







ADVANTAGES

- Can be installed in most slide-in filter banks
- Available in 48 or 102 mm (2" or 4")
- Pre-filter with long life and low initial pressure drop
- Lightweight and easy to install

Application	itable for most areas e-filter for gas turbines, large industrial air compressors, diesel & s engines, generators & enclosures, wind turbines				
Frame	Rigid water resistant cardboard				
Media	Cotton/Synthetic				
Rec. final pressure drop	250 Pa				
Max Temperature (°C)	70°C				
Relative Humidity max	100%				
Installation Options	Universal frame or clip				
Comment	Additional product features: High mechanical strength Rigid, reinforced water-resistant cardboard frame Large media surface Unique radial pleat design Bonded into case to eliminate air bypass Compact Can be fitted directly to a final filter with external clips Different clips are available for mounting combinations with different filters.				

The 30/30GT® has been setting the standard for T3/G4/MERV 8 panel pre-filters. The combination of the unique media, robust construction and pleating technology makes the Camfil 30/30GT a low pressure drop pre-filter that performs well in all situations

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)	ASHRAE 52.2-2017
30/30 GT	G4	Coarse 70%	592x592x95	3400/68	2,5	0,5	MERV 8