MEDIA ROLLS





ADVANTAGES

• Cut to Order

- Available for all kind of applications
- Different efficiencies available

Application	For use as a pre filter in air conditioning, and spraybooth ventilation
Media	Glass fiber;Synthetic;Polyester
Rec. final pressure drop	150 Pa
Max Temperature (°C)	80°C - 100°C
Relative Humidity max	100%



Туре	Media	EN779	ISO 16890	Dimensions WxL (m)	Media Roll Thickness (mm)	Weight (g/m²)	Pressure drop (Pa)	Weight (kg)	Velocity (m/s)
CM-355	Synthetic	G3	Coarse 50%	1,0x20	10	150	30	3,0	1,0
CM-355	Synthetic	G3	Coarse 50%	2,0x20	10	150	30	6,0	1,0
CM-375	Synthetic	G3	Coarse 50%	1,0x20	20	190	30	3,8	1,0
CM-375	Synthetic	G3	Coarse 50%	2,0x20	20	190	30	7,6	1,0
CM-375	Synthetic	G4	Coarse 60%	1,0x20	20	220	40	4,4	1,0
CM-375	Synthetic	G4	Coarse 60%	2,0x20	20	220	40	8,8	1,0
CM-375	Synthetic	G4	Coarse 60%	1,0x20	22	400	45	8,0	1,0
CM-375	Synthetic	G4	Coarse 60%	2,0x20	22	400	45	16,0	1,0
CM-364	Synthetic	G4	Coarse 60%	1,0x20	14-16	220	35	5,0	1,0
CM-364	Synthetic	G4	Coarse 60%	2,0x20	14-16	220	35	9,5	1,0
CM-374	Synthetic	M5	Coarse 85%	2,0x20	18	300	50	12,0	1,0
CDM-600	Synthetic	M5	Coarse 85%	1,0x20	23-25	600	85	12,5	1,0
CDM-600	Polyester	M5	Coarse 85%	2,0x20	23-25	600	85	24,5	1,0

Other sizes and cut pads available on request. Depth: Deviation possible.