

### INSTRUCTIONS FOR:

- Farr 30/30®
- 30/30® Dual 9
- AQ13
- All Aeropleat panel filters



### STORAGE INSTRUCTIONS

- Store filter in vertical position in original box.
- Keep in temperatures between 5°C - 40°C.
- Store in a clean, dry and frost-protected place
- Do not keep filter in direct sunlight.
- Maximum recommended shelf life, before installation, is seven years provided the filter is kept under optimal storage conditions.

### HANDLING INSTRUCTIONS

**Caution:** Handle filter with care. Do not touch the filter media. The slightest touch may lead to leakage. Do not drop filter to prevent severe damage. Avoid liquid spills/splashes on filter.

- Transport and carry vertically.
- Unpacking filters: lift filter by the frame, be careful not to damage the gasket or media. When available, follow instructions on the box!
- Avoid twisting filter frame.
- Large filters may require two people when handling.

### INSTALLATION INSTRUCTIONS

- Keep filter in box as long as possible before installation to avoid damage.
- For vertical installations, make sure filter is fitted with standing pleats.
- Make sure the gasket is not damaged during installation.

### FILTER CHANGE

- Camfil recommends protective equipment such as overalls, gloves and face masks when changing filters.
- Always check local regulations before changing filters
- Filters are not reusable. Used filters should be disposed of according to local regulations.



#### DO NOT

use a blade to open box



#### DO NOT

apply load on filter media



#### DO NOT

touch filter media or push on the grids



#### ONLY HANDLE

large filters by two persons, carry filters vertically



#### ONLY LIFT

panel filters at the corners of the frame