



EPD®

ADVANTAGES

- Innovative pocket design for optimum air distribution
- Conical pockets
- Robust metal header frame
- Low initial pressure drop
- Flat pressure drop curve
- Comprehensive range of standard sizes

Application	Comfort air conditioning applications, pre filter applications
Frame	Galvanised steel
Media	Glass fiber
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
Max airflow	1,25 x nominal flow
Max Temperature (°C)	70°C
Relative Humidity max	100%
Installation Options	Front and side access housings and frames are available

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
1060 592x592x600-6	M5	ePM10 60%	592x592x600	3400/40	6	4,5	1,9	645	B	15	15	27	27	64
1060 490x592x600-5	M5	ePM10 60%	490x592x600	2800/40	5	3,6	1,6		B					
1060 287x592x600-3	M5	ePM10 60%	287x592x600	1700/40	3	2,3	1,1		B					
1060 287x287x600-3	M5	ePM10 60%	287x287x600	800/40	3	1,1	0,7		B					
1060 592x287x600-6	M5	ePM10 60%	592x287x600	1700/40	6	2,3	1,1		B					
1060 592x490x600-6	M5	ePM10 60%	592x490x600	2800/40	6	3,6	1,6		B					
1060 592x892x600-6	M5	ePM10 60%	592x892x600	5000/40	6	6,8	2,4		B					
1060 490x892x600-5	M5	ePM10 60%	490x892x600	4100/40	5	5,7	1,9		B					
1060 287x892x600-3	M5	ePM10 60%	287x892x600	2500/40	3	3,4	1,4		B					
1060 592x592x600-8	M5	ePM10 60%	592x592x600	3400/40	8	6	2,9	522	A	15	15	27	27	64
1060 490x592x600-6	M5	ePM10 60%	490x592x600	2800/40	6	4,5	2,4		A					
1060 287x592x600-4	M5	ePM10 60%	287x592x600	1700/40	4	3	1,5		A					
1060 287x287x600-4	M5	ePM10 60%	287x287x600	800/40	4	1,5	1,0		A					
1060 592x287x600-8	M5	ePM10 60%	592x287x600	1700/40	8	3	1,5		A					
1060 592x490x600-8	M5	ePM10 60%	592x490x600	2800/40	8	4,5	2,4		A					
1060 592x592x520-6	M5	ePM10 60%	592x592x520	3400/45	6	3,8	2	836	C	15	15	27	27	64
1060 490x592x520-5	M5	ePM10 60%	490x592x520	2800/45	5	3	1,8		C					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
1060 287x592x520-3	M5	ePM10 60%	287x592x520	1700/45	3	1,9	1,2		C					
1060 287x287x520-3	M5	ePM10 60%	287x287x520	800/45	3	1,9	0,7		C					
1060 592x287x520-6	M5	ePM10 60%	592x287x520	1700/45	6	1,8	1,2		C					
1060 592x490x520-6	M5	ePM10 60%	592x490x520	2800/45	6	3	1,8		C					
1060 592x592x370-6	M5	ePM10 60%	592x592x370	3400/55	6	2,7	1,8	>1200	E	15	15	27	27	64
1060 490x592x370-5	M5	ePM10 60%	490x592x370	2800/55	5	2,2	1,6		E					
1060 287x592x370-3	M5	ePM10 60%	287x592x370	1700/55	3	1,3	1,2		E					
1060 287x287x370-3	M5	ePM10 60%	287x287x370	800/55	3	0,7	0,8		E					
1060 592x287x370-6	M5	ePM10 60%	592x287x370	1700/55	6	1,3	1,2		E					
1060 592x490x370-6	M5	ePM10 60%	592x490x370	2800/55	6	2,2	1,6		E					
2550 592x592x600-6	M6	ePM2,5 50%	592x592x600	3400/70	6	4,5	1,9	1189	C	40	40	54	54	80
2550 490x592x600-5	M6	ePM2,5 50%	490x592x600	2800/70	5	3,6	1,6		C					
2550 287x592x600-3	M6	ePM2,5 50%	287x592x600	1700/70	3	2,3	1,1		C					
2550 287x287x600-3	M6	ePM2,5 50%	287x287x600	800/70	3	1,1	0,7		C					
2550 592x287x600-6	M6	ePM2,5 50%	592x287x600	1700/70	6	2,3	1,1		C					
2550 592x490x600-6	M6	ePM2,5 50%	592x490x600	2800/70	6	3,6	1,6		C					
2550 592x592x600-8	M6	ePM2,5 50%	592x592x600	3400/60	8	6	2,9	872	B	40	40	54	54	80
2550 490x592x600-6	M6	ePM2,5 50%	490x592x600	2800/60	6	4,5	2,4		B					
2550 287x592x600-4	M6	ePM2,5 50%	287x592x600	1700/60	4	3	1,5		B					
2550 287x287x600-4	M6	ePM2,5 50%	287x287x600	800/55	4	1,5	1,0		B					
2550 592x287x600-8	M6	ePM2,5 50%	592x287x600	1700/60	8	3	1,5		B					
2550 592x490x600-8	M6	ePM2,5 50%	592x490x600	2800/60	8	4,5	2,4		B					
2550 592x592x520-8	M6	ePM2,5 50%	592x592x520	3400/65	8	5,2	2,6	997	C	40	40	54	54	80
2550 490x592x520-6	M6	ePM2,5 50%	490x592x520	2800/65	6	3,9	2,4		C					
2550 287x592x520-4	M6	ePM2,5 50%	287x592x520	1700/65	4	2,5	1,5		C					
2550 287x287x520-4	M6	ePM2,5 50%	287x287x520	800/65	4	1,3	0,8		C					
2550 592x287x520-8	M6	ePM2,5 50%	592x287x520	1700/65	8	2,5	1,5		C					
2550 592x490x520-8	M6	ePM2,5 50%	592x490x520	2800/65	8	3,9	2,4		C					
2550 592x592x370-8	M6	ePM2,5 50%	592x592x370	3400/80	8	3,6	2,4	1167	C	40	40	54	54	80
2550 490x592x370-6	M6	ePM2,5 50%	490x592x370	2800/80	6	2,7	2,1		C					
2550 287x592x370-4	M6	ePM2,5 50%	287x592x370	1700/80	4	1,8	1,5		C					
2550 287x287x370-4	M6	ePM2,5 50%	287x287x370	800/80	4	0,9	0,8		C					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
2550 592x287x370-8	M6	ePM2,5 50%	592x287x370	1700/80	8	1,8	1,5		C					
2550 592x490x370-8	M6	ePM2,5 50%	592x490x370	2800/80	8	2,7	2,1		C					
0160 592x592x600-6	F7	ePM1 60%	592x592x600	3400/85	6	4,5	1,9	1217	C	62	62	71	71	90
0160 490x592x600-5	F7	ePM1 60%	490x592x600	2800/85	5	3,6	1,6		C					
0160 287x592x600-3	F7	ePM1 60%	287x592x600	1700/85	3	2,3	1,1		C					
0160 287x287x600-3	F7	ePM1 60%	287x287x600	800/85	3	1,1	0,7		C					
0160 592x287x600-6	F7	ePM1 60%	592x287x600	1700/85	6	2,3	1,1		C					
0160 592x490x600-6	F7	ePM1 60%	592x490x600	2800/85	6	3,6	1,6		C					
0160 592x592x600-8	F7	ePM1 60%	592x592x600	3400/75	8	6	2,9	946	A	62	62	71	71	90
0160 490x592x600-6	F7	ePM1 60%	490x592x600	2800/75	6	4,5	2,4		A					
0160 287x592x600-4	F7	ePM1 60%	287x592x600	1700/75	4	3	1,5		A					
0160 287x287x600-4	F7	ePM1 60%	287x287x600	800/75	4	1,5	1,0		A					
0160 592x287x600-8	F7	ePM1 60%	592x287x600	1700/75	8	3	1,5		A					
0160 592x490x600-8	F7	ePM1 60%	592x490x600	2800/75	8	4,5	2,4		A					
0160 592x592x520-8	F7	ePM1 60%	592x592x520	3400/85	8	5,2	2,6	1093	B	62	62	71	71	90
0160 490x592x520-6	F7	ePM1 60%	490x592x520	2800/85	6	3,9	2,4		B					
0160 287x592x520-4	F7	ePM1 60%	287x592x520	1700/85	4	2,5	1,5		B					
0160 287x287x520-4	F7	ePM1 60%	287x287x520	800/85	4	1,3	0,8		B					
0160 592x287x520-8	F7	ePM1 60%	592x287x520	1700/85	8	2,5	1,5		B					
0160 592x490x520-8	F7	ePM1 60%	592x490x520	2800/85	8	3,9	2,4		B					
0160 592x592x370-8	F7	ePM1 60%	592x592x370	3400/115	8	3,6	2,4	1670	D	62	62	71	71	90
0160 490x592x370-6	F7	ePM1 60%	490x592x370	2800/115	6	2,7	2,1		D					
0160 287x592x370-4	F7	ePM1 60%	287x592x370	1700/115	4	1,8	1,5		D					
0160 287x287x370-4	F7	ePM1 60%	287x287x370	800/115	4	0,9	0,8		D					
0160 592x287x370-8	F7	ePM1 60%	592x287x370	1700/115	8	1,8	1,5		D					
0160 592x490x370-8	F7	ePM1 60%	592x490x370	2800/115	8	2,7	2,1		D					
0170 592x592x600-6	F7	ePM1 70%	592x592x600	3400/130	6	4,5	1,9	1869	D	71	71	80	80	94
0170 490x592x600-5	F7	ePM1 70%	490x592x600	2800/130	5	3,6	1,6		D					
0170 287x592x600-3	F7	ePM1 70%	287x592x600	1700/130	3	2,3	1,1		D					
0170 287x287x600-3	F7	ePM1 70%	287x287x600	800/130	3	1,1	0,7		D					
0170 592x287x600-6	F7	ePM1 70%	592x287x600	1700/130	6	2,3	1,1		D					
0170 592x490x600-6	F7	ePM1 70%	592x490x600	2800/130	6	3,6	1,6		D					

Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Bags	Media area (m²)	Weight (kg)	Energy (kWh/year)	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
0170 592x592x600-8	F7	ePM1 70%	592x592x600	3400/110	8	6	2,9	1314	C	71	71	80	80	94
0170 490x592x600-6	F7	ePM1 70%	490x592x600	2800/110	6	4,5	2,4		C					
0160 287x592x600-4	F7	ePM1 70%	287x592x600	1700/110	4	3	1,5		C					
0160 287x287x600-4	F7	ePM1 70%	287x287x600	800/110	4	1,5	1,0		C					
0170 592x287x600-8	F7	ePM1 70%	592x287x600	1700/110	8	3	1,5		C					
0170 592x490x600-8	F7	ePM1 70%	592x490x600	2800/110	8	4,5	2,4		C					
0170 592x592x520-8	F7	ePM1 70%	592x592x520	3400/125	8	5,2	2,6	1711	D	71	71	80	80	94
0170 490x592x520-6	F7	ePM1 70%	490x592x520	2800/125	6	3,9	2,4		D					
0170 287x592x520-4	F7	ePM1 70%	287x592x520	1700/125	4	2,5	1,5		D					
0170 287x287x520-4	F7	ePM1 70%	287x287x520	800/125	4	1,3	0,8		D					
0170 592x287x520-8	F7	ePM1 70%	592x287x520	1700/125	8	2,5	1,5		D					
0170 592x490x520-8	F7	ePM1 70%	592x490x520	2800/125	8	3,9	2,4		D					
0170 592x592x370-8	F7	ePM1 70%	592x592x370	3400/170	8	3,6	2,4	>2150	E	71	71	80	80	94
0170 490x592x370-6	F7	ePM1 70%	490x592x370	2800/170	6	2,7	2,1		E					
0170 287x592x370-4	F7	ePM1 70%	287x592x370	1700/170	4	1,8	1,5		E					
0170 287x287x370-4	F7	ePM1 70%	287x287x370	800/170	4	0,9	0,8		E					
0170 592x287x370-8	F7	ePM1 70%	592x287x370	1700/170	8	1,8	1,5		E					
0170 592x490x370-8	F7	ePM1 70%	592x490x370	2800/170	8	2,7	2,1		E					
0185 592x592x600-8	F9	ePM1 85%	592x592x600	3400/160	8	6	2,9	1956	D	87	87	91	91	98
0185 490x592x600-6	F9	ePM1 85%	490x592x600	2800/160	6	4,5	2,4		D					
0185 287x592x600-4	F9	ePM1 85%	287x592x600	1700/160	4	3	1,5		D					
0185 287x287x600-4	F9	ePM1 85%	287x287x600	800/160	4	1,5	1,0		D					
0185 592x287x600-8	F9	ePM1 85%	592x287x600	1700/160	8	3	1,5		D					
0185 592x490x600-8	F9	ePM1 85%	592x490x600	2800/160	8	4,6	2,4		D					
0185 592x592x520-8	F9	ePM1 85%	592x592x520	3400/175	8	5,2	2,6	2266	D	87	87	91	91	98
0185 490x592x520-6	F9	ePM1 85%	490x592x520	2800/175	6	3,9	2,4		D					
0185 287x592x520-4	F9	ePM1 85%	287x592x520	1700/175	4	2,5	1,5		D					
0185 287x287x520-4	F9	ePM1 85%	287x287x520	800/175	4	0,9	0,8		D					
0185 592x287x520-8	F9	ePM1 85%	592x287x520	1700/175	8	2,5	2,4		D					
0185 592x490x520-8	F9	ePM1 85%	592x490x520	2800/175	8	3,9	2,4		D					

Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2019

Energy class: according to Eurovent RS 4/C/001-2019

EPD (Environmental Product Declaration) is available