



ADVANTAGES

- Galvanized filter frame
- 100% leak-free, individually scan tested
- High airflow (2,5 m/s)
- Scanable flat media pack surface

Application	HEPA-filter for high air flows
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Recommended final pressure drop	2x Initial pressure drop
Max. final pressure drop	1000 Pa
Max airflow	Can be calculated on request
Max Temperature (°C)	70°C
Relative Humidity max	100%
Comment	All filter tested acc. to ISO 29463 with individual protocol.



Type	EN1822	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Media area (m ²)	Weight (kg)
DE13-305x610x292-P	H13	305x610x292	1500	250	19,5	13
DE13-457x610x292-P	H13	457x610x292	2450	250	29,7	12
DE13-610x610x292-P	H13	610x610x292	3400	250	39,6	16
DE13-762x610x292-P	H13	762x610x292	3750	250	50,1	20
DE14-305x610x292-P	H14	305x610x292	1500	290	19,5	13
DE14-457x610x292-P	H14	457x610x292	2450	290	29,7	12
DE14-610x610x292-P	H14	610x610x292	3400	290	39,6	16
DE14-762x610x292-P	H14	762x610x292	3750	290	50,1	20

*Other sizes are available on request