ABSOLUTE CE



ADVANTAGES

- 100% leak-free, individually scan tested
-
-
- Low to medium air velocity (up to 1,8 m/s)
- Galvanised metal frame for stability

Application	HEPA filter for standard applications
Frame	Galvanised steel
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot-melt
Sealant	Polyurethane
Recommended final pressure drop	2x Initial pressure drop
Max. final pressure drop	800 Pa
Max airflow	Can be calculated on request
Max Temperature (°C)	70°C
Relative Humidity max	100%
Comment	All filter tested acc. to ISO 29463 with individual protocol. Other options available: MDF frame

Type	EN1822	Dimensions WxHxD (mm)	Airflow/pressure drop (m^3/h/Pa)	Media area (m^2)	Weight (kg)
CET13-305x305x292-P-0R	H13	305x305x292	625/250	5,7	5,6
CET13-305x610x292-P-0R	H13	305x610x292	1260/250	11,7	8,3
CET13-610x610x292-P-0R	H13	610x610x292	2535/250	23,5	13
CET14-305x610x292-P-0R	H14	305x610x292	1045/250	13	8,3
CET14-610x610x292-P-0R	H14	610x610x292	2100/250	26	13
CET14-305x610x292-P-0R-H	H14	305x610x292	1045/250	11,7	8,3
CET14-305x305x292-P-0R	H14	305x305x292	515/250	5,7	5,6
CET14-610x610x292-P-0R-H	H14	610x610x292	2100/250	26	13

Pressure drop: ±10%
Type -P = 1PU gasket placed upstream