



优势

- 可根据客户需要定制非标尺寸
- 锥形袋口, 优化气流阻力
- 效率认证
- 超大滤料面积
- LCC节能优化设计

应用	舒适空调系统应用, 预过滤器应用
外框	镀锌钢
滤材	玻璃纤维
尺寸	过滤器截面尺寸(EN15805)
最大风量	1,25 x 额定风量
最高温度 (°C)	70°C
最大相对湿度	100%
安装选项	可选正面压紧或侧面抽拉式的安装框架.



料号	类型	EN779	ISO16890	尺寸 WxHxD (mm)	风量/初阻力 (m³/h/Pa)	袋数	重量 (kg)	能耗	能耗等级	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
3140009CN	P6	M6	ePM2,5 50%	592x592x520	3400/65	10	2,9	992	C	40	40	54	54	80
3140010CN	Q6	M6	ePM2,5 50%	490x592x520	2800/65	8	2,4		C					
3140011CN	R6	M6	ePM2,5 50%	287x592x520	1700/65	5	1,5		C					
3140029CN	M7 ES	F7	ePM1 60%	592x592x640	3400/60	12	3,3	838	A+	62	62	71	71	90
3140030CN	N7 ES	F7	ePM1 60%	490x592x640	2800/60	10	3		A+					
3140031CN	O7 ES	F7	ePM1 60%	287x592x640	1700/60	6	2		A+					
3140037CN	P7 ES	F7	ePM1 60%	592x592x520	3400/75	10	2,6	895	A	62	62	71	71	90
3140038CN	Q7 ES	F7	ePM1 60%	490x592x520	2800/75	8	2,3		A					
3140039CN	R7 ES	F7	ePM1 60%	287x592x520	1700/75	5	1,6		A					
3140053CN	TM7 ES	F7	ePM1 60%	592x592x370	3400/95	12	2,3	1427	C	62	62	71	71	90
3140054CN	TN7 ES	F7	ePM1 60%	490x592x370	2800/95	10	2,05		C					
3140057CN	M8	F8	ePM1 70%	592x592x640	3400/130	12	2,9							
3140059CN	O8	F8	ePM1 70%	287x592x640	1700/130	6	1,7							
3140065CN	P8	F8	ePM1 70%	592x592x520	3400/160	10	2,41							
3140066CN	Q8	F8	ePM1 70%	490x592x520	2800/160	8	2,03							
3140067CN	R8	F8	ePM1 70%	287x592x520	1700/160	5	1,43							
3140081CN	TM8	F8	ePM1 70%	592x592x370	3400/205	12	2,45							
3140082CN	TN8	F8	ePM1 70%	490x592x370	2800/205	10	2,12							
3140083CN	TO8	F8	ePM1 70%	287x592x370	1700/205	6	1,45							
3145008CN	P9	F9	ePM1 85%	592x592x520	3400/155	10	2,5	1880	D	87	87	91	91	98
3145010CN	Q9	F9	ePM1 85%	490x592x520	2800/155	8	2,4		D					
3145011CN	R9	F9	ePM1 85%	287x592x520	1700/155	5	1,5		D					

最低能耗, kWh/year:参考欧洲准则 4/21-2019
能耗标准: 参考欧洲RS 4/C/001-2019