



ADVANTAGES

- Comprehensive range of standard sizes
- Innovative pocket design for optimum air distribution
- Conical pockets
- Low initial pressure drop
- Flat pressure drop curve.

Application	Prevention of dust and dirt build up on heating/cooling coils within ventilation systems
Frame	Galvanised steel
Media	Synthetic
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 50 Pa or initial pressure drop x3 (whichever is lower)
Max airflow	1,25 x nominal flow
Max Temperature (°C)	70°C
Relative Humidity max	100%
Installation Options	Front and side access housings and frames are available, Type 8 and FC Housings
Comment	Fire rating: DIN 53438 class F1

Art. No.	Type	EN779	ISO16890	Dimensions WxHxD (mm)	Airflow (m3/hr)	Pressure drop (Pa)	Bags	Weight (kg)
3202009	HF 90/35- 592*592-6*580-66	G4	Coarse 60%	592x592x580	3400	30	6	2,6
3202033	HF 90/35- 490*592-5*580-66	G4	Coarse 60%	490x592x580	2800	30	5	2,2
3202016	HF 90/35-287*592-3*580-36	G4	Coarse 60%	287x592x580	1700	30	3	1,5
3200005	HF 90/35-66	G4	Coarse 60%	592x592x360	3400	40	6	2,2
3200006	HF 90/35-56	G4	Coarse 60%	490x592x360	2800	40	5	1,9
3200007	HF 90/35-36	G4	Coarse 60%	287x592x360	1700	40	3	1,3
3100008	HF 90/35-55	G4	Coarse 60%	490x490x360	2334	50	5	1.7

Other dimensions are available on request - All dimensions are nominal
 Pressure drop±15%