



ADVANTAGES

- Comprehensive range of standard sizes.
- Innovative pocket design for optimum air distribution.
- Conical pockets.
- Low initial pressure drop.
- Flat pressure drop curve.

Application	Prefilter for air conditioning and ventilation systems
Frame	Galvanised steel
Media	Synthetic
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 50 Pa or initial pressure drop x3 (whichever is lower)
Max airflow	1,25 x nominal flow
Max Temperature (°C)	70°C
Relative Humidity max	100%
Installation Options	Front and side access housings and frames are available



Type	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow (m ³ /hr)	Pressure drop (Pa)	Bags	Media area (m ²)	Weight (kg)
CO60 592x592x580-6	G4	Coarse 60%	592x592x580	3400	30	6	4,2	2,6
CO60 490x592x580-5	G4	Coarse 60%	490x592x580	2800	30	5	3,5	2,2
CO60 287x592x580-3	G4	Coarse 60%	287x592x580	1700	30	3	2,0	1,5
CO60 592x287x580-6	G4	Coarse 60%	592x287x580	1700	30	6	2	1,5
CO60 287x287x580-3	G4	Coarse 60%	287x287x580	850	30	3	1	0,8
CO60 592x592x360-6	G4	Coarse 60%	592x592x360	3400	40	6	2,6	2,2
CO60 490x592x360-5	G4	Coarse 60%	490x592x360	2800	40	5	2,2	1,9
CO60 287x592x360-3	G4	Coarse 60%	287x592x360	1700	40	3	1,3	1,3
CO60 287x287x360-3	G4	Coarse 60%	287x287x360	800	40	3	0,7	0,7
CO60 592x287x360-6	G4	Coarse 60%	592x287x360	1700	40	6	1,3	1,3

Other dimensions are available on request - All dimensions are nominal