



ADVANTAGES

- Leak free design with welded corners
- Fits Camfil standard MD/MG/MX cleanrooms panels with dry or gel seal
- Noise reducing rounded terminal
- Aesthetic pleasing room side appearance
- Tool free, single person filter installation
- Several mounting options

Application	Turbulent airflow in clean rooms
Frame	Galvanised steel
Gasket	Polyurethane
Installation Options	Filter Mounting: Tool-less multi-height quick release lever clamp for immediate and secured clamping including gasket compression limiter and filter retainer. Housing installation: by removable «universal blocks, for suspension by hangers, or integration into clean room ceiling panels or fitting into T bar grids system.
Comment	Construction: Galvanized steel, fully welded seams Finishing: RAL9010 Aluminium, Optional Connection: By ribbed circular inlet continuous welded on top For Filters: MEGALAM MD/MX/MD PU gasket frame height (66/90/110mm) (to be ordered separately) Control equipment: room side access: 1 port for dp or 100% measurement. Diffusion plates: Perforated or swirl

Type	Dimensions WxHxD (mm)	Filter size HxWxD (Inch)	Con. Ø (mm)
CL-AL-4P4-P-MD-T-C-250-00-AAA0	539x539x260	457x457x66	250
CL-AL-5P5-P-MD-T-C-250-00-AAA0	590x590x260	508x508x66	250
CL-AL-5P5-P-MD-T-C-250-00-AAA0	590x590x260	508x508x66	250
CL-AL-6P6-P-MD-T-C-250-00-AAA0	692x692x260	610x610x66	250
CL-AL-11P5-P-MD-T-C-250-00-AAA0	1190x590x260	508x1108x66	250
CL-AL-12P6-P-MD-T-C-250-00-AAA0	1302x692x260	610x1220x66	250
CL-AL-4P4-P-MX-T-C-250-00-AAA0	539x539x260	457x457x90	250
CL-AL-5P5-P-MX-T-C-250-00-AAA0	590x590x260	508x508x90	250
CL-AL-5P5-P-MX-T-C-250-00-AAA0	590x590x260	508x508x90	250
CL-AL-6P6-P-MX-T-C-250-00-AAA0	692x692x260	610x610x90	250
CL-AL-11PS-P-MX-T-C-250-00-AAA0	1190x590x260	508x1108x90	250
CL-AL-12P6-P-MX-T-C-250-00-AAA0	1302x692x260	610x1220x90	250
CL-AL-4P4-P-MG-T-C-250-00-AAA0	539x539x260	457x457x110	250
CL-AL-5P5-P-MG-T-C-250-00-AAA0	590x590x260	508x508x110	250
CL-AL-5P5-P-MG-T-C-250-00-AAA0	590x590x260	508x508x110	250
CL-AL-6P6-P-MG-T-C-250-00-AAA0	692x692x260	610x610x110	250
CL-AL-11P5-P-MG-T-C-250-00-AAA0	1190x590x260	508x1108x110	250
CL-AL-12P6-P-MG-T-C-250-00-AAA0	1302x692x260	610x1220x110	250
CL-AL-4P4-G-MD-T-C-250-00-AAA0	539x539x260	457x457x71	250
CL-AL-5P5-G-MD-T-C-250-00-AAA0	590x590x260	508x508x71	250
CL-AL-5P5-G-MD-T-C-250-00-AAA0	590x590x260	508x508x71	250
CL-AL-6P6-G-MD-T-C-250-00-AAA0	590x692x260	610x610x71	250
CL-AL-11P5-G-MD-T-C-250-00-AAA0	692x590x260	508x1108x71	250
CL-AL-12P6-G-MD-T-C-250-00-AAA0	1190x692x260	610x1220x71	250
CL-AL-4P4-G-MX-T-C-250-00-AAA0	1302x539x260	457x457x105	250
CL-AL-5P5-G-MX-T-C-250-00-AAA0	539x590x260	508x508x105	250
CL-AL-5P5-G-MX-T-C-250-00-AAA0	590x590x260	508x508x105	250
CL-AL-6P6-G-MX-T-C-250-00-AAA0	590x692x260	610x610x105	250
CL-AL-11P5-G-MX-T-C-250-00-AAA0	692x590x260	508x1108x105	250
CL-AL-12P6-G-MX-T-C-250-00-AAA0	1190x692x260	610x1220x105	250
CL-AL-4P4-G-MG-T-C-250-00-AAA0	1302x539x260	457x457x115	250
CL-AL-5P5-G-MG-T-C-250-00-AAA0	539x590x260	508x508x115	250
CL-AL-5P5-G-MG-T-C-250-00-AAA0	590x590x260	508x508x115	250
CL-AL-6P6-G-MG-T-C-250-00-AAA0	590x692x260	610x610x115	250
CL-AL-11P5-G-MG-T-C-250-00-AAA0	692x590x260	508x1108x115	250
CL-AL-12P6-G-MG-T-C-250-00-AAA0	1190x692x260	610x1220x115	250

*305mm,315mm & 350mm drawn type collar size available on request.

