



ADVANTAGES

- 100% leak-free : individually scan tested
- Strong and airtight frame
- Maximum continuous operating temperature 120°C
- High filter surface area offers low pressure drop for energy savings and longer life
- High Temperature HEPA Filter.
- For very high airflows (up to 3,7 m/s)
- Lightest V-bank steel HEPA in the industry

Application	Industry and hospitals
Frame	Stainless steel;Galvanised steel
Gasket	EPDM
Media	Glass fiber
Separator	Glass fiber
Sealant	Polyurethane
Max Temperature (°C)	120°C
Comment	Temperature: 120°C maximum continuous

Art. No.	Type	Material	EN1822	Dimensions WxHxD (mm)	Airflow/pressure drop (m ³ /h/Pa)	Weight (kg)
1568.01.50	SFR120-E-1300-H13	Galvanised steel	H13	289x595x292	1300/250	12
1567.01.50	SFR120-E-3200-H13	Galvanised steel	H13	595x595x292	3200/250	22
1566.01.00	SFR120-E-1500-H13	Galvanised steel	H13	305x610x292	1500/250	13
1564.01.00	SFR120-E-2500-H13	Galvanised steel	H13	610x610x292	2500/250	19
1561.01.00	SFR120-E-3400-H13	Galvanised steel	H13	610x610x292	3400/250	20
1561.02.00	SFR120-E-4000-H13	Galvanised steel	H13	610x610x292	4000/250	23