



ADVANTAGES

- Zero tempering
- Zero Emission
- Zero Outgasing
- ProSafe + REACH compliance
- H14 in all Temp. ranges $\geq 99,995\%$ at MPPS with DEHS
- Temperature resistant up to 350°C
- Patented construction

Application HEPA filter protection for clean processes at high temperature, especially for Life Science (depyrogenation tunnels, ovens)

Frame Stainless steel

Media Glass fiber

Separator Stainless steel

Sealant Inorganic polymer

Max. final pressure drop 700Pa

Comment Temperature: 350°C with peaks up to 400°C
Remarks: ISO 5 under all production steps. Please note installation and assembly instructions! Other editions on request (with gasket, or sizes)



Type	EN1822	Dimensions WxHxD (mm)	Airflow (m ³ /hr)	Pressure drop (Pa)	Area (m ²)	Frachtgewicht (kg)
DHT14-305x610x150-0-SP	H14	305x610x150	540	310	4,8	8,0
DHT14-610x610x150-0-SP	H14	610x610x150	1180	290	10,4	16,0
DHT14-457x457x150-0-SP	H14	457x457x150	620	300	5,3	9,0
DHT14-762x610x150-0-SP	H14	762x610x150	1500	290	13,1	34,0
DHT14-457x610x150-0-SP	H14	457x610x150	850	300	7,3	12,0
DHT14-305x610x292-0-SP	H14	305x610x292	900	310	9,7	13,0
DHT14-457x610x292-0-SP	H14	457x610x292	1420	300	14,6	19,5
DHT14-610x610x292-0-SP	H14	610x610x292	1960	290	20,7	26,0
DHT14-762x610x292-0-SP	H14	762x610x292	2480	290	25,9	44,0

Pressure drop: $\pm 10\%$