ABSOLUTE V HT120







ADVANTAGES

- 100% leak-free: individually scan tested
- Strong and airtight frame
- Maximum continuous operating temperature 120°C
- High filter surface area offers low pressure drop for energy savings and longer life
- High Temperature HEPA Filter
- For very high airflows (up to 3,7 m/s)
- Lightest V-bank steel HEPA in the industry

Application	Industry and hospitals
Frame	Stainless steel;Galvanised steel
Gasket	EPDM
Media	Glass fiber
Separator	Glass fiber
Sealant	Polyurethane
Max Temperature (°C)	120°C
Installation Options	Mounting systems: FCBL-A housing.
Comment	Temperature: 120°C maximum continuous

Туре	Material	EN1822	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
VEL13-289X595X292-M-HT120	Galvanised steel	H13	289x595x292	1300/250	16	12
VEL13-595X595X292-M-HT120	Galvanised steel	H13	595x595x292	3200/250	38	22
VEL13-305X610X292-M-HT120	Galvanised steel	H13	305x610x292	1500/250	16	13
VEL13-610X610X292-M-HT120	Galvanised steel	H13	610x610x292	2500/250	24	19
VEL13-610X610X292-M-HT120	Galvanised steel	H13	610x610x292	3400/250	33	20
VEXL13-610X610X292-M-HT120	Galvanised steel	H13	610x610x292	4000/250	40	23