



ADVANTAGES

- High filter surface area offers low pressure drop for energy savings and longer life
- High air flow rates
- Large media area
- With stand high temperature up to 120°C

Application	Industry and hospitals
Type	V-Bank Box Filter
Frame	Galvanised steel
Gasket	Neoprene
Media	Glass fiber
Separator	Glassfiber
Sealant	Polyurethane
Temperature max	120°C
Mounting/Frames	Mounting systems: FCBL-A housing
Comment	Gasket: Half-round neoprene 0 15 mm moulded in one piece, 99.995% MPPS (H13 according to EN 1822), 99.99 % 0.3µ Temperature: 120°C maximum continuous

Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
SFR120-E-4000- H13	610x610x292	4000/250	40	23
SFR120-E-3400-H13	610x610x292	3400/250	33	20
SFR120-E-2500- H13	610x610x292	2500/250	24	19
SFR120-E-3200- H13	595x595x292	3200/250	38	22
SFR120-E-1500- H13	305x610x292	1500/250	16	13
SFR120-E-1300- H13	289x595x292	1300/250	16	12

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-14

