


Type 44

High-Velocity Permanent Panel Air Filters



Permanent, cleanable air filter for the elimination of particulate 10-micron and larger



Camfil Type 44 high-velocity air filters are cleanable, low pressure-drop, permanent panels for industrial and commercial applications.

All standard Type 44 air filters include:

- A 16-gauge galvanized steel frame capable of withstanding the rigors of many system removals and filter replacements during standard maintenance cycles
- A media formed of alternate layers of flat and herringbone-crimp galvanized steel screen offering more than 90% efficiency on particles 10-micron and larger
- Flush mitered corners for safe handling and easy installation into filter tracks
- Reinforced internal steel rods to assure filter pack integrity at varying airflows
- Permanent media-to-frame fasteners to assure filter integrity after repeated handlings and cleanings

Additional variations are available as follow:

- Type 44H Includes bail handles on long dimensions of filter
- Type 44R* Includes additional layer of expanded metal on air-entering and airexiting sides
- ype 44 MZ* Hot-dipped galvanized frame and zinc finished media for maritime applications
- Type S4S4* Stainless steel media and frame
- **Type A4A4*** Aluminum media and frame
- Type 48* 18 mesh screen
- **Type 68*** · Six layers, per inch, of 18-mesh screen
- Type 44-68* includes a 2" section of Type 44 media followed by 2" of Type 68 media in 4" depth panel

For oil and mist removal see Camfil ECO Moisture Separator.

^{*} Not available in a 1" panel.



Type 44

High-Velocity Permanent Panel Air Filters

Performance Data

Part Number	Nominal Size (inches)	Actual Size (inches)	Airflow Capacity (cfm)	Pressure Drop (inces w.g.)	Media Area (sq. ft.)
Contact Factory	20 x 16 x 4	19.38 x 15.38 x 4	1110	0.24	85.2
Contact Factory	20 x 20 x 4	19.38 x 19.38 x 4	1390		106.4
Contact Factory	25 x 16 x 4	24.38 x 15.38 x 4	1740		133.0
Contact Factory	25 x 20 x 4	24.38 x 19.38 x 4	1390		106.4
120969-001	24 x 12 x 4	23.38 x 11.38 x 4	1000		76.5
120969-002	24 x 24 x 4	23.38 x 23.38 x 4	2000		153.2
000172-001	20 x 16 x 2	19.38 x 15.38 x 2	1110	0.12	42.6
000172-003	20 x 20 x 2	19.38 x 19.38 x 2	1390		53.2
000172-005	24 x 24 x 2	23.38 x 23.38 x 2	2000		76.6
000172-002	25 x 16 x 2	24.38 x 15.35 x 2	1390		53.2
000172-004	25 x 20 x 2	24.38 x 19.38 x 2	1740		66.5
005661-001	20 x 16 x 1	19.38 x 15.38 x 1	1110	0.10	21.5
005661-005	20 x 20 x 1	19.38 x 19.38 x 1	1390		26.9
005661-007	25 x 20 x 1	24.38 x 19.38 x 1	1740		33.6
005661-003	25 x 16 x 1	24.38 x 15.38 x 1	1390		26.9
Contact Factory	24 x 24 x 1	23.38 x 23.38 x 1	2000		38.7

DATA NOTES:

Type 44 filters are available in a variety of special sizes, contact factory for assistance.

Consult your authorized Camfil Distributor or Representative for installation drawings for built-up bank construction or side-access housings options. Type 44 filters may be used in high temperature applications. Temperature limit is based upon components of construction, consult factory for assistance. For moisture or mist removal see Camfil ECO Moisture Separator.

Specification

1.0 General

- **1.1** Air filter shall be cleanable, all-metal, impingement panel type. The filter shall consist of an all-metal enclosing frame and alternate layers of flat and herringbone-crimp screen media.
- **1.2** Sizes shall be as noted on the enclosed drawings or other supporting materials. Such materials shall also define whether filters are to be oiled or not oiled.

2.0 Construction

2.1 • Filter media shall be multiple layers of flat and herringbone-crimped screen. There shall be at least four screen layers per media pack inch. The media pack shall be permanently fastened to the enclosing frame to maintain filter pack rigidity.

- **2.2** The enclosing frame shall be manufactured of 16-gauge galvanized steel. Frame corners shall be flush, mitered, and reinforced for rigidity.
- ${\bf 2.3}$ Reinforcing rods of 1/8" steel shall assist in maintaining a rigid and durable filter pack.
- **2.4** The filter shall be permanently identified as to the top of the filter for installation guidance.

3.0 Performance

- **3.1** · When installed vertically, the filter shall be 98% efficient on 20-micron size contaminant when operating at a velocity of 500 fpm face velocity. Initial resistance to airflow shall not exceed 0.12" w.g. at 3.6 cfm per square inch of filter face area.
- **3.2** Manufacturer shall provide evidence of facility certification to ISO 9001:2008.

For detailed specifications please consult your local Camfil Distributor or Representative or www.camfil.com.

Camfil has a policy of uninterrupted research, development and product improvement. We reserve the right to change designs and specifications without notice.





Camfil | 1 North Corporate Drive, Riverdale, NJ 07457 | Tel: (973) 616-7300