



ADVANTAGES

- Moulded, stabile and aerodynamic plastic header in one piece
- Rigid self-supporting pockets
- High mechanical strength

Application	Pre-filtration for removing the largest particles in an air conditioning system
Type	Bag Filter
Frame	Plastic moulded
Media	Synthetic
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	150 Pa
Maximum airflow	1,25 x nominal flow
Temperature max	70°C
RH. max	100%
Mounting/Frames	Front and side access housings and frames are available



Type	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Bags	Media area (m ²)	Weight (kg)
HC XLS-66/520	G4	Coarse 60%	592x592x520	3400/30	6	3,7	1,2
HC XLS-65/520	G4	Coarse 60%	592x490x520	2700/30	6	3	1,1
HC XLS-63/520	G4	Coarse 60%	592x287x520	1700/30	6	1,8	0,7
HC XLS-56/520	G4	Coarse 60%	490x592x520	2800/30	5	3	1
HC XLS-36/520	G4	Coarse 60%	287x592x520	1700/30	3	1,8	0,7
HC XLS-66/370	G4	Coarse 60%	592x592x370	3400/35	6	2,6	1
HC XLS-65/370	G4	Coarse 60%	592x490x370	2700/35	6	2,2	0,9
HC XLS-63/370	G4	Coarse 60%	592x287x370	1700/35	6	1,3	0,6
HC XLS-56/370	G4	Coarse 60%	490x592x370	2800/35	5	2,2	0,9
HC XLS-36/370	G4	Coarse 60%	287x592x370	1700/35	3	1,3	0,6

Other dimensions are available on request - All dimensions are nominal

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-07

