



ADVANTAGES

- Incinerable
- Scannable
- Compact design concept
- Very high efficiency

Application	HEPA filter for standard applications
Type	Close Pleated Filter
Frame	MDF
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot Melt
Sealant	Polyurethane
Max. final pressure drop	800 Pa
Temperature max	70°C
RH. max	100%
Comment	Remarks: All filters scan tested acc. EN 1822 Other options available: Galvanized frame



Type	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
CMT13-762x610x292-P	H13	762x610x292	3110/250	27,1	18
CMM13-762x610x292-P	H13	762x610x292	2650/250	20	16,2
CMT13-610x610x292-P	H13	610x610x292	2450/250	21,3	15
CMM13-610x610x292-P	H13	610x610x292	2050/250	16	13
CMT13-457x610x292-P	H13	457x610x292	1800/250	15,8	12
CMM13-457x610x292-P	H13	457x610x292	1470/250	11,5	10
CMM13-457x457x292-P	H13	457x457x292	1050/250	8,5	8
CMT13-457x457x292-P	H13	457x457x292	1260/250	11,6	10
CMM13-305x610x292-P	H13	305x610x292	935/250	7,3	7,2
CMT13-305x610x292-P	H13	305x610x292	1155/250	10,1	9
CMT13-305x305x292-P	H13	305x305x292	535/250	4,7	5
CMM13-305x305x292-P	H13	305x305x292	435/250	3,4	4

Pressure drop: ±10%

Type -P = 1PU gasket placed upstream

Other sizes are available on request

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-13

