



## ADVANTAGES

- Flexible in the dimensions
- Lightweight and installation friendly
- Compliant to VDI 6022
- Scannable
- Rated airflow capacity of up to 3400 m<sup>3</sup>/h 610x610 (H13)
- Halogen free
- Low outgassing

<b>Application</b>	HEPA-Filter for high air flows
<b>Type</b>	Close Pleated Filter
<b>Frame</b>	ABS
<b>Gasket</b>	Polyurethane, endless foamed
<b>Media</b>	Glass fiber
<b>Separator</b>	Hot Melt
<b>Sealant</b>	Polyurethane
<b>Max. final pressure drop</b>	1000 Pa
<b>Temperature max</b>	70°C
<b>RH. max</b>	100%
<b>Comment</b>	Remarks: All filters scan-tested acc. EN 1822:2009

EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Media area (m <sup>2</sup> )	Weight (kg)
H14	762x610x292	4100/290	48,4	15,5
H13	762x610x292	4250/250	48,4	15,5
H14	610x610x292	3200/290	37,8	12
H13	610x610x292	3400/250	37,8	12
H14	305x610x292	1350/290	19,5	8,5
H13	305x610x292	1600/250	19,5	8,5

Other dimensions on demand

Pressure drop: +/- 15%

Type P = gasket on in let air side

Type I = filter with handle and foil

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-25

