



ADVANTAGES

- High efficiency
- Halogen free
- VDI 6022
- Applicable up to 6000 m³/h air flow
- High air flow
- Low pressure drop
- Optimized, compact construction

Application	Efficiency final filtration in air conditioning systems, housings and diffusers
Type	V-Bank Box Filter
Frame	ABS
Gasket	EPDM
Media	Glass fiber
Separator	Hot Melt
Sealant	Polyurethane
Max. final pressure drop	600 Pa
Maximum airflow	Nominal flow rate (if not, efficiency drops)
Temperature max	70°C
RH. max	100%
Mounting/Frames	FKB, 4N, CamSafe2



Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
VGXXL13-762X610X292-M	H13	762x610x292	6000/380	46	14
VGXL14-610x610x292-M	H14	610x610x292	4000/310	38	11
VGXL13-610X610X292-M	H13	610x610x292	4000/250	38	11
VGXXL13-610x610x292-M	H13	610x610x292	5000/380	38	11
VGXL12-610x610x292-M	E12	610x610x292	4000/250	38	11
VGXXL11-610x610x292-M	E11	610x610x292	5000/250	33	11
VGXXL10-610x610x292-M	E10	610x610x292	5000/230	33	11
VGXL13-595x595x292-M	H13	595x595x292	3200/250	37	11
VGXL14-305x610x292-M	H14	305x610x292	1500/310	15	5
VGXL13-305x610x292-M	H13	305x610x292	1500/250	15	5
VGXL12-305x610x292-M	E12	305x610x292	1500/245	15	5
VGXXL11-305x610x292-M	E11	305x610x292	2000/250	13	5
VGXXL10-305x610x292-M	E10	305x610x292	2000/230	13	5
VGXL13-289x595x292-M	H13	289x595x292	1300/250	15	5

Type M = Gasket on one side

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-02-22

