



ADVANTAGES

- Rigid design
- High dust holding capacity
- High quality glass fibre media (HEPA)
- High mechanical strength

Application	HEPA Filter for standard applications
Type	Close Pleated Filter
Frame	Plywood
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Aluminium
Sealant	Polyurethane
Max. final pressure drop	150 mm = 1500 Pa; 292 mm = 2500 Pa
Temperature max	110°C
RH. max	100%
Mounting/Frames	FKB, FKB/D, CamBox
Comment	Remarks: All filter tested acc. EN 1822:2009. Other editions on request

EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
H13	762x610x292	3070/250	28,4	20,5
H13	610x610x292	2435/250	22,5	17,1
H13	457x610x292	1765/250	16,3	14,4
H13	305x610x292	1125/250	10,4	10,4
H13	305x305x292	530/250	5,1	6,4
H13	1220x610x150	3190/250	22,7	18,5
H13	915x610x150	2370/250	16,8	15,1
H13	762x610x150	1955/250	13,9	12,7
H13	610x915x150	2370/250	16,8	15,1
H13	610x610x150	1545/250	11	10,2
H13	575x575x150	1270/250	9,3	9,3
H13	457x457x150	760/250	5,9	8,4
H13	305x610x150	715/250	5,1	7,2
H13	305x305x150	340/250	2,4	3,7

Pressure drop: ±10%

Type -1PU = gasket placed upstream

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-05-21