



### ADVANTAGES

- Rigid design
- High dust holding capacity
- High quality glass fibre media (HEPA)
- High mechanical strength

<b>Application</b>	HEPA Filter for standard applications
<b>Type</b>	Close Pleated Filter
<b>Frame</b>	Plywood
<b>Gasket</b>	Polyurethane, endless foamed
<b>Media</b>	Glass fiber
<b>Separator</b>	Aluminium
<b>Sealant</b>	Polyurethane
<b>Max. final pressure drop</b>	150 mm = 1500 Pa; 292 mm = 2500 Pa
<b>Temperature max</b>	110°C
<b>Mounting/Frames</b>	FKB, FKB/D, CamBox
<b>Comment</b>	Remarks: All filter tested acc. EN 1822:2009. Other editions on request



EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Media area (m <sup>2</sup> )	Weight (kg)
H13	762x610x292	3070/250	28,4	20,5
H13	610x610x292	2435/250	22,5	17,1
H13	457x610x292	1765/250	16,3	14,4
H13	305x610x292	1125/250	10,4	10,4
H13	305x305x292	530/250	5,1	6,4
H13	1220x610x150	3190/250	22,7	18,5
H13	915x610x150	2370/250	16,8	15,1
H13	762x610x150	1955/250	13,9	12,7
H13	610x915x150	2370/250	16,8	15,1
H13	610x610x150	1545/250	11	10,2
H13	575x575x150	1270/250	9,3	9,3
H13	457x457x150	760/250	5,9	8,4
H13	305x610x150	715/250	5,1	7,2
H13	305x305x150	340/250	2,4	3,7

Pressure drop: ±10%

Type -1PU = gasket placed upstream

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-25

