



### ADVANTAGES

- Incinerable
- Compact HEPA filter with header frame

<b>Application</b>	High efficiency final filtration in air conditioning systems and industrial processes
<b>Type</b>	V-Bank Filter
<b>Frame</b>	ABS; header frame, 25mm
<b>Gasket</b>	Polyurethane, endless foamed; Flat gasket
<b>Media</b>	Glass fiber
<b>Separator</b>	Hot Melt
<b>Sealant</b>	Polyurethane
<b>Max. final pressure drop</b>	500 Pa
<b>Temperature max</b>	70°C
<b>RH. max</b>	100%
<b>Comment</b>	Remarks: All filter scan-tested acc. EN 1822:2009 and individually packed in PE-foil. Other editions on request Variant: Filter also available with flat gasket

EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
H13	592x592x292	3000/250	28	10
H13	592x592x292	3000/250	28	6
E11	592x592x292	3000/165	28	10
E11	592x592x292	3000/165	28	10
H13	592x490x292	2450/250	23	6
H13	592x490x292	2450/250	23	6
E11	592x490x292	2450/165	23	6
E11	592x490x292	2450/165	23	6
H13	592x287x292	1350/250	13	3,5
H13	592x287x292	1350/250	13	3,5
E11	592x287x292	1350/165	13	3,5
E11	592x287x292	1350/165	13	3,5

Pressure drop: ± 10%

Type: -0P = gasket placed downstream, -F = gasket placed upstream

Gasket: P = Polyurethane, endless foamed; F = flat gasket

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-25

