CITYSORB







ADVANTAGES

- Ideal for filtering moderate concentrations of most external and internal source pollutants
- Can be used to upgrade existing installations
- Classified according to ISO 10121-3
- Compact filter with molecular media
- Removal of gaseous contaminants

Application	Adsorption of odours and gasses in air conditioning applications.
Frame	Plastic moulded
Gasket	One piece PU gasket (01 in the standard version)
Media	Activated Carbon
Separator	Hot-melt
Sealant	Polyurethane
Dimensions	Filter front dimensions according EN 15805
Max Temperature (°C)	40° C
Relative Humidity max	70%
Installation Options	Front and side access housings and frames are available.

The CitySorb filter utilizes a highly effective broad-spectrum carbon media to ensure the removal of a very wide range of airborne chemicals. The broad spectrum carbon operates with a Rapid Adsorption Dynamics (RAD) mechanism that is specifically designed to be highly efficient against the multiple chemicals that are typically present in low or moderate concentrations in city-centre buildings or other locations.

Туре	ISO 10121 Ozone	ISO 10121 SO ₂	ISO 10121 NO2	ISO 10121 Toluene	Dimensions WxHxD (mm)	Airflow/pressure drop (m ³ /h/Pa)	Media area (m²)	Weight (kg)
OPKCS-242412-01PU	MD 65	vLD 30	vLD 60	MD 75	592x592x292	3400/80	8	10.8
OPKCS-242412-Acid-01PU					592x592x292	3400/80	8	10,8