## **CITYSORB**









## **ADVANTAGES**

- Ideal for filtering moderate concentrations of most external and internal source pollutants
- Can be used to upgrade existing installations
- Classified according to ISO 10121-3
- Compact filter with molecular media
- Removal of gaseous contaminants

| Application           | Adsorption of odours and gasses in air conditioning applications. |
|-----------------------|---|
| Frame                 | Plastic moulded   |
| Gasket                | One piece PU gasket (01 in the standard version)                  |
| Media                 | Activated Carbon  |
| Separator             | Hot-melt  |
| Sealant               | Polyurethane  |
| Dimensions            | Filter front dimensions according EN 15805                        |
| Max Temperature (°C)  | 40° C   |
| Relative Humidity max | 70%   |
| Installation Options  | Front and side access housings and frames are available.          |

The CitySorb filter utilizes a highly effective broad-spectrum carbon media to ensure the removal of a very wide range of airborne chemicals. The broad spectrum carbon operates with a Rapid Adsorption Dynamics (RAD) mechanism that is specifically designed to be highly efficient against the multiple chemicals that are typically present in low or moderate concentrations in city-centre buildings or other locations.

| Type              | ISO 10121 Ozone | ISO 10121 SO <sub>2</sub> | ISO 10121 NO <sub>2</sub> | ISO 10121 Toluene | Dimensions WxHxD (mm) | Airflow/pressure drop (m³/h/Pa) | Media area (m²) | Weight (kg) |
|-------------------|-----------------|---------------------------|---------------------------|-------------------|-----------------------|---------------------------------|-----------------|-------------|
| OPKCS-242412-01PU | MD 65           | vLD 30                    | vLD 60                    | MD 75             | 592x592x292           | 3400/80                         | 8               | 10.8        |
| OPKCS-242012-01PU | MD 65           | vLD 30                    | vLD 60                    | MD 75             | 592x490x292           | 2800/80                         | 6,6             | 9.2         |
| OPKCS-241212-01PU | MD 65           | vLD 30                    | vLD 60                    | MD 75             | 592x287x292           | 1500/80                         | 3,5             | 5.4         |