

# CAMGT BOX TYPE G II

Compact Pleated Filter



## ADVANTAGES

- Resistant to turbulence and high pressure drop
- Easy mounting
- Water resistant media
- Ensures water drainage
- High filtration efficiency
- Low pressure drop also in wet conditions

<b>Application</b>	All installations where safety/reliability is important
<b>Type</b>	Compact Pleated Filter
<b>Frame</b>	Plastic moulded
<b>Gasket</b>	Polyurethane, endless foamed
<b>Media</b>	Glass fiber
<b>Separator</b>	Hot Melt Separator Technology
<b>Rec. final pressure drop</b>	600 Pa
<b>Temperature max</b>	70°C
<b>Comment</b>	Additional information: XL version available on request. Profile placed at 292 mm depth for clamping, i.e for fastener spring type C-80.



CamGT Box Type G is a high-capacity filter for turbomachinery. Thanks to the unique design, its performance is maintained in humid or wet conditions, guaranteeing a long lifetime and a good filter economy.

Type	EN779	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Media area (m <sup>2</sup> )	Weight (kg)	ASHRAE 52.2-2017
Std	F7		592x592x315	4250/115	19	7,6	MERV 13
Std	F8		592x592x315	4250/140	19	7,6	MERV 14
Std	F9		592x592x315	4250/145	19	7,6	MERV 15
Std		E10	592x592x315	4250/215	19	7,6	

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.  
2019-05-15