



ADVANTAGES

- Better pulsability due to surface loading media technology
- Recommended as a pre-filter, not recommended as a final filter
- Self-cleaning cartridge filter with long filter life
- Extends final filter life when used as a prefilter

Application	Desert and arctic environments, heavy dust load areas Pre-filter for gas turbines, large industrial air compressores, diesel & gas engines, generators & enclosures
Frame	Galvanised steel;Stainless steel AISI 304L, 316L
Gasket	Polyurethane, endless foamed;EPDM
Media	Synthetic
Rec. final pressure drop	1000 Pa
Max Temperature (°C)	70° C
Pleat	Dimple

Caps: Galvanized (Standard), stainless steel (AISI304 / 316) or powder-coated
Fire rating: Available according to DIN 4102-b2
Holding frames: Various on request. Sizes: Co-cy, cy-cy, Tenkay and others on request

Comment

Additional product features:
Self-cleaning air filter cartridges
Medium filtration efficiency
Effective dust holding capacity
Built-in structural strength
Galvanized metal finish
Media protected by metal liners on both sides
Tenkays are available with the Gold Cone option for improved pulsing.
Other filter sizes are available. Contact us for more information.
Retrofit filters are also available for all competitor housings.
Filter wraps available on demand

CamPulse filter systems are designed to protect rotating machinery in high dust load environments. The cleaning system provides continuous operation and stable pressure even in extremely dusty environments.

Type	EN779	Length (mm)	Diameter (mm)	Length 2 (mm)	Diameter 2 (mm)	Airflow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
CamPulse Co/Cyl	M6	660	445/324	660	324	2500/175	46	13,5