



## ADVANTAGES

- High mechanical strength
- Compliant to EC 1935:2004
- Compliant to VDI 6022 / ISO 846
- Specially designed for process safety (Food & Life Science applications)
- Rigid self supporting pockets
- Moulded, stable and aerodynamic plastic header in one piece

<b>Application</b>	Pre-filtration for removing the largest particles in an air conditioning system
<b>Type</b>	Bag Filter
<b>Frame</b>	Plastic
<b>Media</b>	Synthetic
<b>Dimensions</b>	Filter front dimensions according EN 15805
<b>Rec. final pressure drop acc. EN 13053</b>	150 Pa
<b>Maximum airflow</b>	1,25 x nominal flow
<b>Temperature max</b>	70°C
<b>RH. max</b>	100%
<b>Mounting/Frames</b>	Front and side access housings and frames are available



Food and Beverage or Life-Science activities have set new standards in product quality and therefore require specific characteristics regarding process definition.

Camfil, as the leader in clean air solutions and air filtration, has developed the complete ProSafe™ range of products designed for the most demanding processes, including safety, traceability and audits requirement.

Type	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Bags	Media area (m <sup>2</sup> )	Weight (kg)
4/520	G4	Coarse 60%	592x592x520	3400/30	6	3,7	1,2
4/520	G4	Coarse 60%	592x490x520	2700/30	6	3,0	1,1
4/520	G4	Coarse 60%	592x287x520	1700/30	6	1,8	0,7
4/520	G4	Coarse 60%	490x592x520	2800/30	5	3,0	1
4/520	G4	Coarse 60%	287x592x520	1700/30	3	1,8	0,7
4/370	G4	Coarse 60%	592x592x370	3400/35	6	2,6	1
4/370	G4	Coarse 60%	592x490x370	2700/35	6	2,2	0,9
4/370	G4	Coarse 60%	592x287x370	1700/35	6	1,3	0,6
4/370	G4	Coarse 60%	490x592x370	2800/35	5	2,2	0,9
4/370	G4	Coarse 60%	287x592x370	1700/35	3	1,3	0,6

Other dimensions are available on request - All dimensions are nominal

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-06

