



## ADVANTAGES

- Versatile air diffusion possibilities
- Non-unidirectional airflow for clean room
- Interchangeable grids
- Tool-free access to filter
- Damper adjustable from room side
- Economical design
- Simplified filter maintenance : no tools
- Control ports from room side
- For pressure drop and integrity
- High airflow per unit

<b>Application</b>	Turbulent airflow clean rooms and hospitals
<b>Type</b>	Terminal Filter Housing
<b>Mounting/Frames</b>	CamSeal housing
<b>Comment</b>	<p>Installation: In T bar grid, suspended or fixed by brace Construction: Plenum : galvanized steel ; clean part : white painted RAL9010 oven backed For filters: Megalam MG HFC HD high airflow HEPA panels Mounting of filters: Clamping device with gasket compression limitation Pressure drop: 1 standard, access from room side Connection: By collar on lateral side or superior Damper: Adjustable from room side Options: Swirl, perforated flush, adjustable vanes or 4 way grids to be ordered separately Note: All grids are hinged Closure: Instant magnetic studs</p>

Type	EN1822	Dimensions WxHxD (mm)	Con. Ø (mm)	Airflow/Pressure drop @ 0,45 m/s (m³/h/Pa)	Media area (m²)	Weight (kg)
CSL-5P5-LS-C250D		595x595x452	250			9,6
CSL-5P5-LS-C250		595x595x452	250			10,4
CSL-3P3-LS-C160D		392x392x362	160			7.0
CSL-3P3-LS-C160		392x392x362	160			6,8
CSL-5P5-TS-C250		595x595x270	250			6.7
CSL-3P3-TS-C160		392x392x270	160			5.9
MG14 HFC HD-2G / 5P5	H14	503x503x104		1370250	6,5	6,5
MG10 HFC HD-2G / 5P5	E10	503x503x104		1500250	12	6,5
MG14 HFC HD-2G / 3P3	H14	300x300x104		490250	5,3	3,5
MG10 HFC HD-2G / 3P3	E10	300x300x104		500250	4	3,5
CSL-4W-5P5		549x549x35				1.8
CSL-4W-3P3		347x347x35				1.0
CSL-SW-5P5		549x549x20				2.9
CSL-SW-3P3		346x346x20				1.3
CSL-PF-5P5		549x549x16				2,5
CSL-PF-3P3		346x346x16				1.0

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-01-15

