## **CAMBOX S**





## **ADVANTAGES**

- Incl. maintenance bag for noncontact filter changes
- Pressure resistant up to 5000 Pa
- Integrated filter seal seat testing acc. KTA 3601
- Quick and easy installation

| Application | Separation of hazardous dusts and gases, which occur in isotope laboratories, laboratories cabinet, radiology departments, isolation or epidemiological stations   |
|-------------|--|
| Comment     | Housing epoxy painted (decontaminable): Epoxy painted (RAL 7037) Housing stainless steel: Stainless steel 1.4301 Standard design: Spiro pipe connection DN 315, clamping device made of stainless steel 1.4301 Options: Flange DN 315, pressure tapping point, base frame Filter: Airopac, Absolute and Micretain for CamBox S/D; Activated carbon filter for CamBox S/D AK Remarks: Leak-tight testing instrument DSP-3 (please see page "Housing accessories") |

| Dimensions WxHxD (mm) | Weight (kg) |
|-----------------------|-------------|
| 710x366x717           | 29          |
| 710x474x717           | 35          |
| 710x614x717           | 48          |
| 710x366x717           | 29          |
| 710x474x717           | 35          |
| 710x614x717           | 48          |
| 710x614x717           | 48          |
| 710x614x717           | 48          |

Other equipments or multistage filter systems available on request