



## ADVANTAGES

- Large surface area
- Rigid design concept
- High dust holding capacity
- Low pressure drop
- Robust metal header frame

<b>Application</b>	Air conditioning applications and preparatory filtration in clean-rooms
<b>Type</b>	Compact Pleated Filter
<b>Frame</b>	Galvanised steel
<b>Gasket</b>	Polyurethane
<b>Media</b>	Glass fiber
<b>Separator</b>	Aluminium
<b>Sealant</b>	Polyurethane
<b>Dimensions</b>	Filter front dimensions according EN 15805
<b>Rec. final pressure drop acc. EN 13053</b>	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
<b>Maximum airflow</b>	1,15 x nominal flow
<b>Temperature max</b>	110°C
<b>RH. max</b>	100%
<b>Mounting/Frames</b>	Front and side access housings and frames are available



Model Name	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Media area (m <sup>2</sup> )	Weight (kg)
3CPM-242412-60	M6	ePM10 70%	610x610x292	2500/45	15,8	8,9
3CPM-HF-242412-60	M6	ePM10 70%	592x592x292	2500/60	13,3	9
3CPM-122412-60	M6	ePM10 70%	305x610x292	1300/50	7,7	5,3
3CPM-HF-122412-60	M6	ePM10 70%	287x592x292	1300/80	6,2	5,7
3CPM-24246-60	M6	ePM10 70%	610x610x150	1300/15	7,8	5,1
3CPM-HF-24246-60	M6	ePM10 70%	592x592x150	1300/25	6,5	5,8
3CPM-12246-60	M6	ePM10 70%	305x610x150	650/15	3,8	3,2
3CPM-HF-12246-60	M6	ePM10 70%	287x592x150	650/30	2,9	3,8
3CPM-242412-90	F7	ePM1 55%	610x610x292	2500/70	15,8	8,9
3CPM-HF-242412-90	F7	ePM1 55%	592x592x292	2500/95	13,3	9
3CPM-122412-90	F7	ePM1 55%	305x610x292	1300/80	7,7	5,3
3CPM-HF-122412-90	F7	ePM1 55%	287x592x292	1300/110	6,2	5,7
3CPM-24246-90	F7	ePM1 55%	610x610x150	1300/50	7,8	5,1
3CPM-HF-24246-90	F7	ePM1 55%	592x592x150	1300/60	6,5	5,8
3CPM-12246-90	F7	ePM1 55%	305x610x150	650/50	3,8	3,2
3CPM-HF-12246-90	F7	ePM1 55%	287x592x150	650/65	2,9	3,8
3CPM-242412-95	F9	ePM1 80%	610x610x292	2000/85	15,6	8,9
3CPM-HF-242412-95	F9	ePM1 80%	592x592x292	1800/80	12,6	9
3CPM-122412-95	F9	ePM1 80%	305x610x292	1050/85	7,8	5,3
3CPM-HF-122412-95	F9	ePM1 80%	287x592x292	950/80	5,7	5,7

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-05-22