



## ADVANTAGES

- Tested resistance to decon and cleaning procedures
- High air flow, low pressure drop
- Individual test certificate acc. to EN1822:2009
- Optimizing waste management: compactable, incinerable, lightweight
- Ideal for CREO energy optimization
- Recommended for food & beverage and life science industries
- Hygienic product acc. to VDI6022
- Microbial inert components acc. to ISO846
- Food contact approved acc. to EC1935:2004
- Free of harmful chemical components: halogen-free, bisphenol-free, formaldehyde-free, phthalate-free



<b>Application</b>	EPA/HEPA final filtration for air conditioning systems of sensitive process industries like life science or food and beverage
<b>Type</b>	V-Bank Box Filter
<b>Frame</b>	ABS
<b>Gasket</b>	Polyurethane, endless foamed
<b>Media</b>	Glass fiber
<b>Separator</b>	Hot Melt
<b>Sealant</b>	Polyurethane
<b>Max. final pressure drop</b>	600 Pa
<b>Temperature max</b>	70°C
<b>RH. max</b>	100%
<b>Mounting/Frames</b>	Front and side access filter frames. Terminal housings and safe change systems
<b>Comment</b>	Certificates and further information: <a href="http://www.camfil.com/prosafe">www.camfil.com/prosafe</a>

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
VGXL14-762X610X292-P-PS	H14	762x610x292	4800/310	46	14
VGXXL13-762X610X292-P-PS	H13	762x610x292	6000/380	46	14
VGXXL11-762X610X292-P-PS	E11	762x610x292	6000/250	46	14
VGXL14-610X610X292-P-PS	H14	610x610x292	4000/310	38	11
VGXXL13-610X610X292-P-PS	H13	610x610x292	5000/380	38	11
VGXL13-610X610X292-P-PS	H13	610x610x292	4000/240	38	11
VGXXL11-610X610X292-P-PS	E11	610x610x292	5000/250	33	11
VGXL14-305X610X292-P-PS	H14	305x610x292	1500/310	15	5
VGXL13-305X610X292-P-PS	H13	305x610x292	1500/250	15	5
VGXXL11-305X610X292-P-PS	E11	305x610x292	2000/250	13	5

Type P = gasket one sided

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-02-22

