



ADVANTAGES

- Quick and easy mounting
- Robust metal header frame
- Meets the demands of EN 779:2012 and ISO 16890
- Tapered bags for optimised performance

Application	Comfort air conditioning applications, prefilter applications
Type	Bag Filter
Frame	Galvanised steel
Media	Glass fiber
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
Maximum airflow	1,25 x nominal flow
Temperature max	70°C
RH. max	100%
Mounting/Frames	Front and side access housings and frames are available
Comment	Remarks: Also available with plastic frame, 25mm



Type	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Bags	Media area (m²)	Weight (kg)	Energy consumption	Energy class	ePM1	ePM1min	ePM2,5	ePM2,5min	ePM10
UF7	F7	ePM1 50%	592x592x600	3400/85	8	6	2,6	1020	B	54	54	66	66	88
A7	F7	ePM1 50%	592x592x600	3400/95	6	4,5	2,4	1144	C	54	54	66	66	88
UF7-65	F7	ePM1 50%	592x490x600	2800/85	8	4,5	2,4		B					
A7-65	F7	ePM1 50%	592x490x600	2800/95	6	3,6	2,1		C					
UF7-63	F7	ePM1 50%	592x287x600	1700/85	8	3	1,5		B					
A7-63	F7	ePM1 50%	592x287x600	1700/95	6	2,3	1,5		C					
UG7	F7	ePM1 50%	490x592x600	2800/85	6	4,5	2,4		B					
B7	F7	ePM1 50%	490x592x600	2800/95	5	3,6	2,1		C					
UH7	F7	ePM1 50%	287x592x600	1700/85	4	3	1,5		B					
C7	F7	ePM1 50%	287x592x600	1700/95	3	2,3	1,5		C					
UH7-33	F7	ePM1 50%	287x287x600	800/85	4	1,5	0,8		B					
C7-33	F7	ePM1 50%	287x287x600	800/95	3	1,1	0,8		C					
UF7/520	F7	ePM1 50%	592x592x520	3400/95	8	5,2	2,6	1087	C	54	54	66	66	88
A7/520	F7	ePM1 50%	592x592x520	3400/100	6	3,7	2	1518	D	54	54	66	66	88
UF7-65/520	F7	ePM1 50%	592x490x520	2800/95	8	3,9	2,4		C					
A7-65/520	F7	ePM1 50%	592x490x520	2800/100	6	3	1,8		D					
UF7-63/520	F7	ePM1 50%	592x287x520	1700/95	8	2,5	1,5		C					
A7-63/520	F7	ePM1 50%	592x287x520	1700/100	6	1,8	1,2		D					
UG7/520	F7	ePM1 50%	490x592x520	2800/95	6	3,9	2,4		C					
B7/520	F7	ePM1 50%	490x592x520	2800/100	5	3	1,8		D					
UH7/520	F7	ePM1 50%	287x592x520	1700/95	4	2,5	1,5		C					
C7/520	F7	ePM1 50%	287x592x520	1700/100	3	1,8	1,2		D					
UH7-33/520	F7	ePM1 50%	287x287x520	800/95	4	1,3	0,8		C					
C7-33/520	F7	ePM1 50%	287x287x520	800/100	3	0,9	0,7		D					
UF7/370	F7	ePM1 50%	592x592x370	3400/125	8	3,6	2,4	1563	D	54	54	66	66	88
A7/370	F7	ePM1 50%	592x592x370	3400/135	6	2,6	1,8	2186	E	54	54	66	66	88
UF7-65/370	F7	ePM1 50%	592x490x370	2800/125	8	2,7	2,1		D					
A7-65/370	F7	ePM1 50%	592x490x370	2800/135	6	2,2	1,6		E					
UF7-63/370	F7	ePM1 50%	592x287x370	1700/125	8	1,8	1,5		D					
A7-63/370	F7	ePM1 50%	592x287x370	1700/135	6	1,3	1,2		E					
UG7/370	F7	ePM1 50%	490x592x370	2800/125	6	2,7	2,1		D					
B7/370	F7	ePM1 50%	490x592x370	2800/135	5	2,2	1,6		E					
UH7/370	F7	ePM1 50%	287x592x370	1700/125	4	1,8	1,5		D					
C7/370	F7	ePM1 50%	287x592x370	1700/135	3	1,3	1,2		E					
UH7-33/370	F7	ePM1 50%	287x287x370	800/125	4	0,9	0,8		D					
C7-33/370	F7	ePM1 50%	287x287x370	800/135	3	0,6	0,8		E					

Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2018

Energy class: according to Eurovent RS 4/C/001-2019

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.
2019-05-23