STANDARD-FLO





ADVANTAGES

- Innovative pocket design for optimum air distribution
- Conical pockets
- Robust metal header frame
- Economy version to achieve ePM1 filtration.

Fan

• Low initial pressure drop

| Application | Comfort air conditioning applications, prefilter applications |
|---|---|
| Frame | Galvanised steel |
| Media | Glass fiber |
| Dimensions | Filter front dimensions according EN 15805 |
| Rec. final pressure drop acc. EN 13053 | Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower) |
| Max airflow | 1,25 x nominal flow |
| Max Temperature (°C) | 70°C |
| Relative Humidity max | 100% |
| Installation Options | Front and side access housings and frames are available |
| Comment | Remarks: Also available with plastic frame, 25mm |
| | |

| Туре | EN779 | ISO 16890 | Dimensions WxHxD (mm) | Airflow/pressure drop (m ³ /h/Pa) | Bags | Media area (m²) | Weight (kg) | Energy class | |
|--------|-------|-----------|-----------------------|--|------|-----------------|-------------|--------------|--|
| B7/520 | F7 | ePM1 50% | 490x592x520 | 2800/100 | 5 | 3 | 1,8 | D | |
| _ | | | | | | | | | |

Energy Consumption, kWh/year: Calculated according to Eurovent Guideline 4/21-2019 Energy class: according to Eurovent RS 4/C/001-2019