


ADVANTAGES

- Individually VOC outgassing tested
- Multiple media types can be combined into the same filter
- Low pressure drop
- High media cleanliness

Application	Clean room recirculation air, clean room make up air
Type	Box Filter & Header Filter
Frame	Galvanised steel
Sealant	Polyurethane
Temperature max	10 - 40°C
RH. max	30% - 70%
Particle cleanliness	ISO Class 6
Comment	Outgassing: Individually outgassing tested for VOC emissions



Type	Target contaminant	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Weight (kg)
NXDPB2C3L3	Bases, Acids, Organics	592x592x292	3300/140	20
NXDPL3	Organics	592x592x292	3300/50	15
NXDPC3	Acids	592x592x292	3300/50	15
NXDPB2	Bases	592x592x292	3300/50	15
NXDPB2C3L3	Bases, Acids, Organics	287x592x292	1600/140	12
NXDPL3	Organics	287x592x292	1600/50	10
NXDPC3	Acids	287x592x292	1600/50	10
NXDPB2	Bases	287x592x292	1600/50	10

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.
2019-05-14