



ADVANTAGES

- Robust construction for reliable operation
- Rigid frame for demanding applications. Fire classified M1
- Low pressure drop media resulting in low energy costs

Application	Pre filter for comfort air conditioning applications
Type	Pleated Panel
Frame	Metal
Media	Cotton/Synthetic
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	150 Pa
Maximum airflow	1,1 x nominal flow
Temperature max	70°C
RH. max	100%
Mounting/Frames	Front and side access housings and frames are available



Model Name	Type	EN779	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
AeroPleat Metal	Metal	G4	Coarse 65%	610x610x50	3600/55	1,2	2,3
AeroPleat Metal	Metal	G4	Coarse 65%	592x592x50	3400/55	1,1	2,2
AeroPleat Metal	Metal	G4	Coarse 65%	500x625x50	3000/55	1,0	2,3
AeroPleat Metal	Metal	G4	Coarse 65%	500x500x50	2400/55	0,8	1,7
AeroPleat Metal	Metal	G4	Coarse 65%	400x500x50	1900/55	0,6	1,5
AeroPleat Metal	Metal	G4	Coarse 65%	305x610x50	1800/55	0,6	1,7
AeroPleat Metal	Metal	G4	Coarse 65%	287x592x50	1650/55	0,5	1,7

Other dimensions are available on request - All dimensions are nominal

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-02-26

