CAM-FLO GT HYBRID







ADVANTAGES

•

- Fully incinerable
 - Suitable for harsh environments
- Recommended choice for gas turbine pre-filtration
- Pre-filter with long life and low initial and stable pressure drop
- Mechanical efficiency and coalescing properties extend life of final filters

Application	Suitable for most installations, including turbulent airflows and harsh environments Pre-filter for gas turbines, large industrial air compressors, diesel & gas engines, generators & enclosures							
Frame	Galvanised steel							
Gasket	Flat gasket							
Media	Hybrid Synthetic and Glass Technology							
Rec. final pressure drop	450 Pa							
Max Temperature (°C)	70°C							
Relative Humidity max	100%							
Installation Options	Separate bank, from upstream or downstream side							
Comment	Additional product features: Optimized filter area with conical filter bags Durable media Superior dust holding capacity Low and stable pressure drop Fully incinerable Hybrid media technology Synthetic pre-filter layer for high mechanical strength and coalescing properties A fine glass fiber layer provides high mechanical efficiency and dust holding capacity with stable dP in high humidity Galvanized frame, also available in a plastic frame Available in half - and special size filters on request							

The Cam-Flo Hybrid is a new generation of premium bag filters for gas turbines that utilize the breakthrough Hybrid media technology to combine glass fiber and synthetic fibers. The results is a smart solution for an extended filter life, a stable and predictable performance, and most of all, carefree operations. Self-supporting bags and a unique design make this filter an excellent pre-filter and coalescer choice for turbomachinery applications.

Туре	EN779	ISO 16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Bags	Media area (m ²	2) Weight (kg)	ePM1	PM1mir	ePM2,5	ePM2,5mii	n ePM10/	ASHRAE 52.2-2017
Cam-Flo GT Hybrid T	6 M6	ePM2,555%	592x592x640	4250/80	10 (std)	7,5	2.45						MERV 11
Cam-Flo GT Hybrid T	7 F7	ePM160%	592x592x640	4250/90	10 (std)	7,5	2.45	60	60	71	71	90	MERV 13
Cam-Flo GT Hybrid T	9 F9	ePM1 85%	592x592x640	4250/165	10								