



ADVANTAGES

- Individual certificate
- Proven product, the factory controlled characteristics of which are maintained after handling and transportation
- Parameters integrated into internal software for customer simulation
- High efficiency filter for safety and protection uses
- Individual test of the leak rate

Application	When BOBI is required to proceed to the VOC filter change
Type	Vee Cell Module
Frame	Stainless steel; Steel, painted
Gasket	½ round 15 mm moulded neoprene foam
Comment	Media: 50 mm (2 inch) bed depth of chromium-free activated carbon; vibrated and tamped to meet leakage requirements Gas to trap: Volatil Organic Compounds Impregnation: None Particle size: 2 mm extruded Relative Humidity: < 50% Temperature: 80°C maximum continues Carbon impregnation: none Adsorbent volume (liters): full size 65 liters +/- 40 kg - half size 32,5 liters +/- 20 kg Controls: Individual test run for leakages (< 2,5 x 10 ⁻⁴) and pressure drop

Model Name	Material	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Weight (kg)
ActiCarb VOC	Stainless steel	610x610x292	1800/300	71
ActiCarb VOC	Galvanised steel	610x610x292	1800/300	71
ActiCarb VOC	Stainless steel	305x610x292	900/300	43
ActiCarb VOC	Galvanised steel	305x610x292	900/300	43

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-02-14

