



ADVANTAGES

- High efficiency
- Flexibility in size
- HL3 & HL4 are individually tested
- High air flow applications
- High quality glass fibre media

Application	HEPA-filter for high air flows
Type	Close Pleated Filter
Frame	Galvanised steel
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot Melt
Sealant	Polyurethane
Temperature max	70°C
RH. max	100%
Comment	Fire rating: DIN 53438 Class Fl



Model Name	Type	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
DE14-762x610x292-P0-S			762x610x292	3300/250		20
DE13-762x610x292-P0-S			762x610x292	3750/250		20
DE14-610x610x292-P0-S			610x610x292	2600/250		16
DE13-610x610x292-P0-S			610x610x292	3000/250		16
	DE13-305x610x292-P	H13	305x610x292	1500/250	19,5	10,5
DE14-305x610x292-P0-S			305x610x292	1300/250		13
DE13-305x610x292-P0-S			305x610x292	1500/250		13

*Other sizes are available on request

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-25

