



ADVANTAGES

- Low pressure drop
- Ergonomic handle
- For optimised air filtration in cleanrooms
- High air flow
- Applicable up to 5000 m³/h air flow

Application	Efficiency final filtration in air conditioning systems, housings and diffusers
Type	V-Bank Box Filter
Frame	Galvanised steel
Gasket	EPDM
Media	Glass fiber
Separator	Hot Melt
Sealant	Polyurethane
Max. final pressure drop	600 Pa
Temperature max	70°C
RH. max	100%
Mounting/Frames	FKB, FKB/D, CamBox
Comment	Remarks: Special versions on request (e.g. stainless steel frame or high temperature version 120°C)

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
VEXL14-610x610x292-M	H14	610x610x292	3500/270	40	16,5
VEXL13-610x610x292-M	H13	610x610x292	4000/250	40	16,5
VEXL12-610x610x292-M	E12	610x610x292	4000/250	40	16,5
VEXXL11-610x610x292-M	E11	610x610x292	5000/250	35,5	23
VEXL10-610x610x292-M	E10	610x610x292	4000/250	21	13
VEXL13-595x595x292-M	H13	595x595x292	3200/250	38	15,5
VEXL12-595x595x292-M	E12	595x595x292	3200/250	38	22
VEXL10-595x595x292-M	E10	595x595x292	4200/250	38	13
VEXL14-305x610x292-M	H14	305x610x292	1400/280	16	8,5
VEXL13-305x610x292-M	H13	305x610x292	1500/250	16	8,5
VEXXL11-305x610x292-M	E11	305x610x292	2000/250	14	14
VEXL12-305x610x292-M	E12	305x610x292	1500/250	16	8,5
VEXL10-305x610x292-M	E10	305x610x292	2000/250	14	8,5
VEXL13-289x595x292-M	H13	289x595x292	1300/250	16	8,5
VEXL12-289x595x292-M	E12	289x595x292	1300/250	16	12
VEXL10-289x595x292-M	E10	289x595x292	1700/250	16	8,5

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-01-25

