



ADVANTAGES

- High Temperature
- Ergonomic handle
- Low pressure drop

Application	Sterilization tunnels and ovens
Type	V-Bank Filter
Frame	Stainless steel
Gasket	Neoprene
Media	Glass fiber
Separator	Glassfiber
Sealant	Silicon HT
Rec. final pressure drop	400
Max. final pressure drop	400
Temperature max	230°C in continuous operation
Temperature max. (peak)	250°C
RH. max	100%
Mounting/Frames	FKB, FKB/D, CamBox
Comment	Gasket: Half-round neoprene 0 15 mm moulded in one piece, 99.995% MPPS (H13 according to EN 1822), 99.99 % 0.3µ Temperature: 230°C maximum continuous

Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
SFR230-ER-3000-H13-610x610x292	610x610x292	3000/275	40,0	25
Absolute V HT230-H13-610x610x292	610x610x292	3000/275	40,0	25
SFR230-ER-1400-H13-610x610x292	610x610x292	1400/130	40,0	25
SFR230-ER-3000-H13-610x610x292	610x610x292	3000/275	40,0	25
SFR230-ER-1500-H13-305x610x292	305x610x292	1500/275	19,0	14
SFR230-ER-700-H13-305x610x292	305x610x292	700/130	19,0	14
SFR230-ER-700-H13-305x610x292	305x610x292	700/130	19,0	14

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-05-10