



## ADVANTAGES

- High Temperature
- Low pressure drop
- Ergonomic handle

<b>Application</b>	Sterilization tunnels and ovens
<b>Type</b>	V-Bank Filter
<b>Frame</b>	Stainless steel
<b>Gasket</b>	Neoprene
<b>Media</b>	Glass fiber
<b>Separator</b>	Glassfiber
<b>Sealant</b>	Silicon HT
<b>Max. final pressure drop</b>	400
<b>Temperature max</b>	230°C in continuous operation
<b>Temperature max. (peak)</b>	250°C
<b>RH. max</b>	100%
<b>Mounting/Frames</b>	FKB, FKB/D, CamBox
<b>Comment</b>	Gasket: Half-round neoprene 0 15 mm moulded in one piece, 99.995% MPPS (H13 according to EN 1822), 99.99 % 0.3µ Temperature: 230°C maximum continuous

Model Name	Dimensions WxHxD (mm)	Air Flow/pressure drop (m <sup>3</sup> /h/Pa)	Media area (m <sup>2</sup> )	Weight (kg)
SFR230-ER-3000-H13-610x610x292	610x610x292	3000/275	40,0	25
SFR230-ER-3000-H13-610x610x292	610x610x292	3000/275	40,0	25
SFR230-ER-1400-H13-610x610x292	610x610x292	1400/130	40,0	25
SFR230-ER-3000-H13-610x610x292	610x610x292	3000/275	40,0	25
SFR230-ER-1500-H13-305x610x292	305x610x292	1500/275	19,0	14
SFR230-ER-700-H13-305x610x292	305x610x292	700/130	19,0	14
SFR230-ER-700-H13-305x610x292	305x610x292	700/130	19,0	14

[www.camfil.com](http://www.camfil.com)

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-25

