



ADVANTAGES

- Easy and safe-handling
- Hygienic filter media acc. to ISO846
- Optimized for low energy consumption
- High temperature resistance
- Lightweight frame design

Application	High temperature air-handling units
Type	V-Bank Filter
Frame	Galvanised steel
Gasket	EPDM
Media	Glass fiber
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop	F7: 200 Pa, F8-F9: 300 Pa
Temperature max	120°C
RH. max	100%
Mounting/Frames	Front and side access housings and frames are available.



Model Name	EN779	EN1822	ISO16890	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
HT7	F7		ePM1 55%	592x592x285	3400/75	19.8	9
HT7	F7		ePM1 55%	592x592x285	3400/75	19.8	9
HT7	F7		ePM1 55%	592x592x285	3400/75	19.8	9
HT8	F8		ePM1 70%	592x592x285	3400/85	19.8	9
HT8	F8		ePM1 70%	592x592x285	3400/85	19.8	9
HT8	F8		ePM1 70%	592x592x285	3400/85	19.8	9
HT9	F9		ePM1 80%	592x592x285	3400/100	19.8	9
HT9	F9		ePM1 80%	592x592x285	3400/100	19.8	9
HT9	F9		ePM1 80%	592x592x285	3400/100	19.8	9
HT10		E10	ePM1 95%	592x592x285	4000/260	19.8	9
HT10		E10	ePM1 95%	592x592x285	4000/260	19.8	9
HT10		E10	ePM1 95%	592x592x285	4000/260	19.8	9

EPDM gasket code: 00 = no gasket; 01 = downstream; 10 = upstream

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.
2019-04-23

