Camfil Farr 30/30[®] High Capacity MERV 8/8A and ePM₁₀ Pleated Panel Air Filter



Last longer than any other pleated panel filter available...Guaranteed!

CLEAN AIR SOLUTIONS

€camfi

Your first line of defense

Dust particles dancing on the beams of light streaming through a window may look beautifully surreal, but the reality is that those same dust particles and most that are too small to see with the naked eye pose alarming risks to people, animals, equipment, commerce and industries. These particles contain a mixture of both solid and liquid organic and inorganic substances consisting of sulfates, nitrates, ammonia, sodium chloride, black carbon, mineral dust and more. The most damaging particles are those with a diameter of 10 microns or less ($< PM_{10}$).

So where do you begin to filter this attack?

Your first line of defense for HVAC equipment and people starts with Camfil's Farr 30/30 pleated panel filter. Used as a stand alone or as a prefilter, the Farr 30/30, proven to be the industry's best value for medium efficiency filtration, has an Energy Cost Index (ECI) of five stars—the highest performance rating available. The Farr 30/30® is an excellent choice when applied as the only filter in a system to keep coils clean, maintain efficiency, and protect building occupants from contaminants such as pollen, plant spores, atmospheric dusts and other indoor air irritants. Life of final filters can be extended by capturing larger contaminants and allowing the final filter to concentrate on removing smaller particles.

Performing at MERV 8/8A and ePM₁₀ under ASHRAE and ISO filter testing standards respectively, the Farr 30/30 media is manufactured from a proprietary blend of fibers that uses a mechanical particle capture principle which does not require an electret charge. The electret charge of the competitors' coarse fiber filters dissipates over time resulting an earlier high pressure drop and loss of efficiency long before what should be a full life cycle. The Farr 30/30 offers the longest life and lowest average pressure drop while in service over the life of the filter...Guaranteed! The media is lofted to a uniform, high-loft depth offering a lower resistance to airflow so fan energy is dramatically reduced, ensuring the longest life of any pleated filter available and saving replacement cost in the long run. Backed with a welded wire grid, spot-welded on one-inch centers, the media is formed into a radial pleat for uniform dust loading and maintains media stability through varying airflows. Housed in a high wet-strength beverage board frame, the thickest board in the industry, filter bypass is virtually eliminated as the media is bonded to the frame. Diagonal supports are bonded to each pleat to maintain pleat spacing and add stability to the bridge-style engineered pack. The Farr 30/30 is guaranteed to 2.0" w.g. of pressure filter without failure. Costly filter blowouts and compromised cleanliness of HVAC systems is dramatically reduced if not eliminated.



Farr 30/30[®]

Camfil Farr 30/30[®] High Capacity MERV 8/8A and ePM₁₀ Pleated Panel Air Filter

The choice is clear, Camfil's Farr 30/30[®] is the proven industry leader

Best performance, lasts longer, reduces energy costs and waste. Guaranteed!



Composite minimum particle size removal efficiencies of the Camfil Farr 30/30 above include concomitants that can foul coils and HVAC systems such as bacteria, dusts and common allergens related to health discomfort.

Science and Quality Control Standards

Each media roll is tested to ensure high level performance characteristics. Every Farr 30/30 is inspected for pleat spacing uniformity, structural integrity, and proper adhesive bonding of diagonal supports to the pleat apexes. Frequent samples are pulled from our ISO certified quality manufacturing process of ASHRAE 52.2 testing in our world-class testing facility.

Unprecedented Industry Guarantee

We are so confident in our filter's performance, we are the only manufacturer that GUARANTEES our filters will hold their rated efficiency for the entire life of the filter. If our filters don't outlast and outperform



your current filters, we'll replace them, FREE. For guarantee details and a distributor list, visit www.camfil.us.



The above photos of the same filter (front and back) clearly illustrate the huge dust holding capacity of the Farr 30/30. This filter was in service from 12/7/2014 through 6/25/2015 in the Williamson Medical Center in Franklin, TN. Even through six and a half months and harsh drywall demolition, the exhaust side remained clean — no bleed-through or reduction in efficiency.

The Farr 30/30 can capture a wide variety of contaminants with this wide range of efficiency — bacteria, paper dust, mold, skin flakes and many others. Consult your local Camfil office for contaminant size guidance and Farr 30/30 application.

Features of Camfil's Farr 30/30®

- Exclusive media
- Radial pleat design
- Welded wire media backing
- MERV 8 and MERV-A of 8 when tested per ASHRAE Standard 52.2^a
- High wet-strength beverage board frame
- Bonding between the frame and the media
- · Bonding between the media and the diagonal supports



Camfil's multiple testing facilities ensure consistent product performance and adherence to air filtration testing standards ASHRAE 52.2 and ISO 16890 for MERV and MERV-A, and ePM_{10} published values respectively.

1 North Corporate Drive | Riverdale, NJ 07457 Phone: 973.616.7300 | Fax: 973.616.7771 camfilusa@camfil.com

WWW.Camfil.us For further information, please contact your nearest Camfil office.