



ADVANTAGES

- Fast, simple filterchange
- Compact design
- Long lifespan
- High efficiency

Application	Air filter for ventilation units
Type	V-Bank Box Filter
Frame	Galvanised steel
Gasket	EPDM
Media	Glass fiber
Separator	Hot Melt
Sealant	Polyurethane
Dimensions	Filter front dimensions according EN 15805
Rec. final pressure drop acc. EN 13053	Initial pressure drop + 100 Pa or initial pressure drop x3 (whichever is lower)
Maximum airflow	1,1 x nominal flow
Temperature max	70°C
RH. max	100%



Model Name	Type	EN779	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Media area (m ²)	Weight (kg)
Opakair	OPR120-E-F7	F7	610x610x292	4500/110	20	18
Opakair	OPR-E-F7	F7	610x610x292	4500/85	20	18
Opakair	OPR-E-F7	F7	305x610x292	2250/85	10	9
Opakair	OPR120-E-F8	F8	610x610x292	4500/130	20	18
Opakair	OPR-E-F8	F8	610x610x292	4500/110	20	18
Opakair	OPR-E-F8	F8	305x610x292	2250/110	10	9
Opakair	OPR-E-F9	F9	610x610x292	3400/140	20	18
Opakair	OPR-E-F9	F9	305x610x292	1700/140	10	9

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-05-16