



ADVANTAGES

- Very high efficiency
- Scannable
- Compact design concept

Application	HEPA filter for standard applications
Type	Box Filter
Frame	Galvanised steel
Gasket	Polyurethane, endless foamed
Media	Glass fiber
Separator	Hot Melt
Sealant	Polyurethane
Max. final pressure drop	800 Pa
Maximum airflow	Nominal flow rate (if not, efficiency drops)
Temperature max	70°C
RH. max	100%
Comment	Remarks: All filters scan tested acc. EN 1822 Other options available: Galvanized frame

Model Name	EN1822	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Media area (m²)	Weight (kg)
	H14	610x610x292	2100/250	26	13
	H14	610x610x292	2100/250	26	13
CET13-610x610x292-PR	H13	610x610x292	2535/250	23,5	13
	H14	305x610x292	1045/250	11,7	8,29
	H14	305x610x292	1045/250	13	8,29
CET13-305x610x292-PR	H13	305x610x292	1260/250	11,7	8,29
CET14-0305/0305/0292-P2	H14	305x305x292	515/250	5,7	5,63
CET13-305x305x292-PR	H13	305x305x292	625/250	5,7	5,63

Pressure drop: ±10%

Type -P = 1PU gasket placed upstream

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2019-03-25

