

□

ADVANTAGES

- Rigid design
- High efficiency filtration (EPA)
- High dust holding capacity
- High mechanical strength

| | |
|------------------------|---|
| Type | Box Filter |
| Frame | Plywood |
| Gasket | Polyurethane, endless foamed; Flat gasket |
| Media | Glass fiber |
| Separator | Aluminium |
| Sealant | Polyurethane |
| Temperature max | 110°C |
| RH. max | 100% |

| Model Name | EN1822 | Dimensions WxHxD (mm) | Air Flow/pressure drop (m ³ /h/Pa) | Media area (m ²) | Weight (kg) |
|-------------|--------|-----------------------|---|------------------------------|-------------|
| 7D-1000-1PU | E11 | 610x610x292 | 1965/125 | 22,5 | 17 |
| 7D-450-1PU | E11 | 305x610x292 | 900/125 | 10,4 | 10,4 |
| 7D-200-1PU | E11 | 305x305x292 | 405/125 | 4,9 | 6,4 |
| 7D-600-1PU | E11 | 610x610x150 | 1500/125 | 11 | 10,2 |
| 7D-220-1PU | E11 | 305x610x150 | 690/125 | 5,1 | 6,2 |
| 7D-110-1PU | E11 | 305x305x150 | 310/125 | 2,4 | 3,7 |

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-05-22