## **ABSOLUTE 1FRK-V**







## **ADVANTAGES**

- Maximum continuous operating temperature 350°C
- Individually scan tested at 20°C
- High mechanical stability
- Reinforced stainless steel frame
- High temperature HEPA Filter
- Filter class H13 acc. to EN 1822 (at 20°C)
- High air velocity (1,5m/s)

Application	Protection for clean processes at high temperature			
Frame	Reinforced stainless steel			
Gasket	Glass Fiber			
Media	Glass fiber			
Separator	Aluminium			
Sealant	Ceramic			
Max. final pressure drop	500 Pa			
Max Temperature (°C)	350°C			
Relative Humidity max	100%			
Comment	Please note installation and assembly instructions! Due to the different thermal expansion coefficients of the individual filter components the ceramic potting may form cracks during the tempering process. At operating temperature (350 °C) these filters have an overall efficiency of 99,97% at 0,3 µm, leackages are possible.			

Type	EN1822	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
1FRKV-220-1W	H13	305x610x150	540/250	10,3
1FRKV-300-1W	H13	457x457x150	620/250	11,2
1FRKV-600-1W	H13	610x610x150	1180/250	13,5
1FRKV-980-1W	H13	915x610x150	1780/250	18,3
1FRKV-450-1W	H13	305x610x292	900/250	18
1FRKV-725-1W	H13	457x610x292	1420/250	21,4
1FRKV-1000-1W	H13	610x610x292	1960/250	23,4
1FRKV-1250-1W	H13	762x610x292	2480/250	25,9

Modell -1W = Gasket upstream (standard) Modell -01W = Gasket downstream

Modell -2W = Gasket both sides

Modell -0 = no gasket Other editions on request