



### ADVANTAGES

- Unique radial pleat design
- Bonded into case to eliminate air bypass
- Compact
- High mechanical strength
- Rigid, reinforced water resistant cardboard frame
- Large media surface

<b>Application</b>	Suitable for most areas
<b>Frame</b>	Water resistant cardboard
<b>Media</b>	Cotton/Synthetic
<b>Rec. final pressure drop</b>	250 Pa
<b>Max Temperature (°C)</b>	70°C
<b>Relative Humidity max</b>	100%
<b>Installation Options</b>	Universal frame or clip
<b>Comment</b>	Additional information: Different clips available for mounting combinations with different filters.



The 30/30GT® has been setting the standard for G4/MERV 8 panel pre-filters. The combination of the unique media, robust construction and pleating technology makes the Camfil 30/30GT a low pressure drop pre-filter that performs well in all situations

Art. No.	Type	EN779	ASHRAE 52.2-2017	ISO16890	Dimensions WxHxD (mm)	Airflow/pressure drop (m³/h/Pa)	Weight (kg)
540F-FG070205001	30/30 GT 24x24x4	G4	MERV 8	Coarse 70%	594x594x95	4250/85	1.1
*540F-FG402312001	30/30 GT 24x24x4	G4	MERV 8	Coarse 70%	594x594x95	4250/85	1.1
*540F-FG402312001A	30/30 GT Special 24x24x4	G4	MERV 8	Coarse 70%	592x592x95	4250/85	1.1
*540F-FG402312005	30/30 GT Special 24x24x3.5	G4	MERV 8	Coarse 70%	592x592x89	4250/85	1.1
540F-FG406332005	30/30 GT Dual 10 24x24x4	G4	MERV 9	ePM10 50%	592x592x95	4250/85	1.1

\*with gasket

\*Available in Dual 10 media