



ADVANTAGES

- High media cleanliness
- Low pressure drop
- Wide range of dimensions

Application	Clean room recirculation air, clean room make up air
Type	Box Filter
Frame	Stainless steel;Galvanised steel;Aluminium
Sealant	Polyurethane
Temperature max	40°C
RH. max	30% - 70%
Particle cleanliness	ISO Class 6
Comment	Gasket position: 01 - downstream, 10 - upstream Outgassing: Individually outgassing tested for VOC emissions on request



Type	Dimensions WxHxD (mm)	Air Flow/pressure drop (m ³ /h/Pa)	Weight (kg)
NXPC A3	305x610x292	1100/60	8
NXPC A3	595x595x292	2600/60	15
NXPC A3	289x595x292	1100/60	8
NXPC A3	287x592x292	1100/60	8
NXPC B2	305x610x292	1100/60	8
NXPC B2	595x595x292	2600/60	15
NXPC B2	289x595x292	1100/60	8
NXPC A3	610x610x292	2600/60	15
NXPC C3	287x592x292	1100/60	8
NXPC B2	610x610x292	2600/60	15
NXPC B2	592x592x292	2600/60	15
NXPC B2	287x592x292	1100/60	8
NXPC C3	610x610x292	2600/60	15
NXPC A3	592x592x292	2600/60	15
NXPC C3	305x610x292	1100/60	8
NXPC C3	595x595x292	2600/60	15
NXPC C3	289x595x292	1100/60	8
NXPC C3	592x592x292	2600/60	15
NXPC L3	610x610x292	2600/60	15
NXPC L3	305x610x292	1100/60	8
NXPC L3	595x595x292	2600/60	15
NXPC L3	289x595x292	1100/60	8
NXPC L3	592x592x292	2600/60	15
NXPC L3	287x592x292	1100/60	8

For media choice, please refer to Gigapleat NXPH

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.

2019-09-16