



ADVANTAGES

- Individually VOC outgassing tested
- Multiple media types can be combined into the same filter
- Low pressure drop
- High media cleanliness

Application	Clean room recirculation air, clean room make up air
Type	Box Filter & Header Filter
Frame	Galvanised steel
Sealant	Polyurethane
Temperature max	40°C
RH. max	30% - 70%
Particle cleanliness	ISO Class 6
Comment	Gasket Position: 01 - downstream, 10 - upstream Outgassing: Individually outgassing tested for VOC emissions



Type	Target contaminant	Dimensions WxHxD (mm)	Air Flow/pressure drop (m³/h/Pa)	Weight (kg)
NXDP ABV	Bases, Acids, Organics	592x592x292	3300/140	20
NXDP V	Organics	592x592x292	3300/50	15
NXDP A	Acids	592x592x292	3300/50	15
NXDP B	Bases	592x592x292	3300/50	15
NXDP ABV	Bases, Acids, Organics	287x592x292	1600/140	12
NXDP V	Organics	287x592x292	1600/50	10
NXDP A	Acids	287x592x292	1600/50	10
NXDP B	Bases	287x592x292	1600/50	10

Other media combinations available on request
 Pressure drop based on DH (Box type) frame

www.camfil.com

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice.
 2019-10-10

